


# MTi-G-710

- Xsens' high-performance product line
- 0.2 deg in roll/pitch, 0.8 deg in heading accuracy
- Complete SDK and development kits available

The MTi-G-710 is an Inertial Measurement Unit (IMU) with an integrated GNSS receiver. It features vibration-rejecting gyroscopes, and offers high-quality position, velocity, acceleration, and orientation, even in challenging environments.

The MTi-G-710 supports optimized temperature calibration, high-frequency position and orientation output, and has configurable output settings for synchronization with any third-party device.

The MTi-G-710 is supported by the MT Software Suite, which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms.



- White label and OEM integration options available
- 3D models available on request
- Available online via Digi-Key, Mouser, Farnell and local distributors

## Sensor fusion performance

Roll, Pitch	0.2 deg RMS
Yaw/Heading	0.8 deg RMS
Strapdown Integration (SDI)	1.0 m (1 $\sigma$ STD)
Velocity	0.05 m/s (1 $\sigma$ STD)

## Gyroscope

Standard full range	450 deg/s
In-run bias stability	10 deg/h
Bandwidth (-3dB)	415 Hz
Noise Density	0.01 $^{\circ}$ /s/ $\sqrt$ Hz
g-sensitivity (calibr.)	0.003 $^{\circ}$ /s/g

## Accelerometer

Standard full range	20 g
In-run bias stability	15 $\mu$ g
Bandwidth (-3dB)	375 Hz
Noise Density	60 $\mu$ g/ $\sqrt$ Hz

## Magnetometer

Standard full range	+/- 8 G
Total RMS noise	0.5 mG
Non-linearity	0.2%
Resolution	0.25 mG

## GNSS Receiver

Brand	u-blox
Model	MAX-M8
RTCM input port	n/a

## Barometer

Standard full range	300-1100 hPa
Total RMS noise	3.6 Pa
Resolution	~0.08m

## Mechanical

IP-rating	IP67
Operating Temperature	-40 to 85 $^{\circ}$ C
Casing material	Aluminum
Mounting orientation	No restriction, full 360 $^{\circ}$ in all axes
Dimensions	57x41.90x23.60 mm
Connector	Fischer SV
Weight	58 g

## Electrical

Input voltage	3V3, 4.5V-34V
Power consumption (typ)	660 mW

## Interfaces / IO

Interfaces	USB, RS232, RS422, UART
Sync Options	SyncIn, SyncOut, ClockSync
Protocols	Xbus, ASCII (NMEA)
Clock drift	1 ppm
Output Frequency	up to 2kHz
Built-in-self test	Yes

## Software Suite

GUI (Windows/Linux)	MT Manager Firmware updater, Magnetic Field Mapper
SDK (Example code)	C++, C#, python, Matlab, Nucleo, public source code
Drivers	LabVIEW, ROS, GO
Support	BASE by XSENS: online manuals, community and knowledge base