

MTi-680G

- Rugged, IP68 rated RTK GNSS/INS
- 0.2 deg roll/pitch & sub-meter level position accuracy
- u-blox ZED F9 RTK GNSS receiver

The MTi-680G is a Global Navigation Satellite System/Inertial Navigation System (GNSS/INS) with integrated Real-Time Kinematic (RTK) receiver, with a rugged housing with IP68 protection. The RTK feature improves your positional data from meter-level to centimeter-level accuracy. This easy-to-use RTK-enhanced GNSS/INS module is designed for seamless integration with other equipment.

The MTi-680G is supported by the MT Software Suite, which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms.



- White label and OEM integration options available
- 3D models available on request
- Available online via Digi-Key, Mouser, Farnell and local distributors

Sensor Fusion Performance

| | |
|-------------|-------------|
| Roll, Pitch | 0,2 deg RMS |
| Yaw/Heading | 0.5 deg RMS |
| Position | 1cm CEP |
| Velocity | 0.05m/s RMS |

Gyroscope

| | |
|-------------------------|---------------|
| Standard full range | 2000 deg/s |
| In-run bias stability | 8 deg/h |
| Bandwidth (-3dB) | 520 Hz |
| Noise Density | 0.007 °/s/√Hz |
| g-sensitivity (calibr.) | 0.001 °/s/g |

Accelerometer

| | |
|-----------------------|-------------------|
| Standard full range | 10 g |
| In-run bias stability | 10 (x,y) 15(z) µg |
| Bandwidth (-3dB) | 500 Hz |
| Noise Density | 60 µg/√Hz |

Magnetometer

| | |
|---------------------|---------|
| Standard full range | +/- 8 G |
| Total RMS noise | 1 mG |
| Non-linearity | 0.2% |
| Resolution | 0.25 mG |

RTK GNSS Receiver

| | |
|-----------------|-----------------|
| Brand | u-blox |
| Model | ZED F9 |
| RTCM input port | RTCM 3.3, RS232 |

Barometer

| | |
|---------------------|------------------|
| Standard full range | 300-1250 hPa |
| Total RMS noise | 1.2 Pa |
| Relative accuracy | +/- 8 Pa (~0.5m) |

Mechanical

| | |
|-----------------------|---|
| IP-rating | IP68 |
| Operating Temperature | -40 to 85 °C |
| Casing material | Aluminum |
| Mounting orientation | No restriction, full 360° in all axes |
| Dimensions | 56.50x40.90x36.75 mm |
| Connector | Main: ODU (AMC HD 12 pins) RTCM: ODU (AMC HD 4 pins) Antenna: SMA |
| Weight | 98 g |

Electrical

| | |
|-------------------------|------------|
| Input voltage | 4.5 to 24V |
| Power consumption (typ) | <1 W |

Interfaces / IO

| | |
|--------------------|----------------------------|
| Interfaces | CAN, RS232 |
| Sync Options | SyncIn, SyncOut, ClockSync |
| Protocols | Xbus, ASCII (NMEA) or CAN |
| Clock drift | 1ppm |
| Output Frequency | 2 kHz, 400 Hz SDI |
| Built-in-self test | Yes |

Software Suite

| | |
|---------------------|---|
| GUI (Windows/Linux) | MT Manager Firmware updater, Magnetic Field Mapper |
| SDK (Example code) | C++, C#, python, Matlab, Nucleo, public source code |
| Drivers | LabVIEW, ROS, GO |
| Support | BASE by XSENS: online manuals, community and knowledge base |