

## Specification Sheet

Part Number: 151-00838



Designed for use with MBTS(-S), MBTH(-S), and MBTSFC stainless steel ties, or 18 through 120 pound nylon cable ties to provide stability when securing bundles.

Secures with a single screw providing quick installation.

Stainless Steel Tie Mount, .21" Hole Dia, .39" Max Tie Width, Grade 316 SST, ML, 100/pkg

**Article Number** 151-00838

**Type** SSPC5

**Color** Metal (ML)

**Quantity Per** bag

**Product Description** Stainless steel P-mounts provide a robust and extremely durable fixing solution for a wide range of applications. With a 10mm slot width and either a 4mm, 5mm or 6mm fixing hole, this '2-way' mount can be installed quickly and easily with a single screw or bolt providing excellent performance and a high pull force. Designed for heavy duty applications and made out of a high grade stainless steel 316 material, these P-mounts provide resistant to chemicals, salt spray, extreme weather conditions and corrosion. They are also non-flammable, ensuring a highly secure and safe fixing solution.

|  |  |
|--|--|
| <b>Short Description</b>                     | Stainless Steel Tie Mount, .21" Hole Dia, .39" Max Tie Width, Grade 316 SST, ML, 100/pkg |
| <b>Global Part Name</b>                      | SSPC5-SS316-ML   |
| <b>Length L (Imperial)</b>                   | 0.91   |
| <b>Length L (Metric)</b>                     | 23.0   |
| <b>Fixation Method</b>                       | Screw Mounting and Rivet   |
| <b>Width W (Imperial)</b>                    | 0.40   |
| <b>Width W (Metric)</b>                      | 10.2   |
| <b>Cable Ties</b>                            | MBTS(-S) and MBTH(-S) stainless steel ties   |
| <b>Height H (Imperial)</b>                   | 0.18   |
| <b>Height H (Metric)</b>                     | 4.5  |
| <b>Cable Tie Width Max (Imperial)</b>        | 0.39   |
| <b>Cable Tie Width Max (Metric)</b>          | 10.0   |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.21   |
| <b>Mounting Hole Diameter D (Metric)</b>     | 5.3 mm   |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 5.3  |

|                                     |                                     |
|-------------------------------------|-------------------------------------|
| <b>Material</b>                     | Stainless Steel (SS316)             |
| <b>Material Shortcut</b>            | SS316                               |
| <b>Flammability</b>                 | Non-burning                         |
| <b>Halogen Free</b>                 | Yes                                 |
| <b>Operating Temperature</b>        | -112°F to +1000°F (-80°C to +538°C) |
| <b>Reach Compliant (Article 33)</b> | Yes                                 |
| <b>ROHS Compliant</b>               | Yes                                 |
| <b>Package Quantity (Imperial)</b>  | 100                                 |
| <b>Package Quantity (Metric)</b>    | 100                                 |
| <b>Customs Number</b>               | 7326908695                          |