

## Specification Sheet

Part Number: 115-00030



The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.

Additional design feature on the head allows excess strap to be tucked away after installation.

Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66HIRH(S), Black, 5/pkg

<b>Article Number</b>	115-00030
<b>Type</b>	SpeedyTie (RTT750HR)
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	pcs.
<b>Product Description</b>	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.
<b>Short Description</b>	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66HIRH(S), Black, 5/pkg
<b>Global Part Name</b>	SpeedyTie (RTT750HR)-PA66HIRH(S)-BK

<b>Minimum Tensile Strength (Imperial)</b>	200.0
<b>Minimum Tensile Strength (Metric)</b>	888.0
<b>Length L (Imperial)</b>	29.6
<b>Length L (Metric)</b>	752.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.51
<b>Width W (Metric)</b>	13.0
<b>Bundle Diameter Min (Imperial)</b>	1.6
<b>Bundle Diameter Min (Metric)</b>	40.0
<b>Bundle Diameter Max (Imperial)</b>	8.3
<b>Bundle Diameter Max (Metric)</b>	210.0
<b>Thickness T (Imperial)</b>	0.075
<b>Thickness T (Metric)</b>	1.9

<b>Material</b>	Polyamide 6.6, high impact modified, scan black (PA66HIR(S))
<b>Material Shortcut</b>	PA66HIR(S)
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	5
<b>Package Quantity (Metric)</b>	5
<b>Customs Number</b>	3926909988