

M12-PCB-SMT-2PC-8P-ACOD-M-STR-SHLD



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---------------------------------------------------------------------------------------|
| Part number | 21 03 321 1802 |
| Specification | M12-PCB-SMT-2PC-8P-ACOD-M-STR-SHLD |
| HARTING eCatalogue | https://b2b.harting.com/21033211802 |

Identification

| | |
|---------------|-------------------------|
| Category | Connectors |
| Series | Circular connectors M12 |
| Element | PCB adapter |
| Specification | Straight |

Version

| | |
|--------------------|------------------------------------|
| Termination method | Reflow soldering termination (SMT) |
| Gender | Male |
| Shielding | Shielded |
| Number of contacts | 8 |
| Coding | A-coding |
| Details | Order housings separately |

Technical characteristics

| | |
|-----------------------|---------------------------|
| Rated current | 2 A |
| Rated voltage | 30 V |
| Pollution degree | 3 |
| Overvoltage category | III |
| Insulation resistance | $>10^8 \Omega$ |
| Contact resistance | $\leq 10 \text{ m}\Omega$ |
| Ambient temperature | -40 ... +85 °C |
| Mating cycles | ≥ 100 |



Pushing Performance

Technical characteristics

| | |
|-----------------|---------------|
| Isolation group | I (600 ≤ CTI) |
|-----------------|---------------|

Material properties

| | |
|-------------------------------------------|--------------------------------------------------------|
| Material (insert) | Liquid crystal polymer (LCP) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Au over Ni Mating side |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 0d7d3693-d625-47ab-934a-d241bf72c86e |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Nickel Lead |

Specifications and approvals

| | |
|----------------|-----------------|
| Specifications | IEC 61076-2-101 |
|----------------|-----------------|

Commercial data

| | |
|--------------------------------|------------------------------------------|
| Packaging size | 25 |
| Net weight | 3.4 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27460201 PCB connector (board connector) |