

## Liquid Flux No-Clean in 15ml (0.5z) Squeeze Bottle w/tip

### Product Highlights

A liquid flux that is non-flammable  
No-Clean  
Water-Based, leaves no residues  
VOC Free, Halide Free, Rosin Free  
Ideal for all rework, solder, and de-solder applications  
Excellent wetting  
Easily cleaned with isopropyl alcohol (IPA)  
Can be used with Leaded and Lead-Free applications  
**RoHS 3 and REACH compliant**



### Specifications

Flux Type:	No-Clean Liquid Flux (for Leaded and Lead-Free applications)
Flux Classification:	ORL0
VOC Content:	VOC Free
Specific Gravity:	1.01
Packaging:	15ml Squeeze Bottle
Shelf Life:	Refrigerated >24 months, Unrefrigerated >24 months

### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

### Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

### Cleaning

This is a no-clean liquid flux, post-use cleaning is not required.

Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):	Yes
RoHS 3 Directive 2015/863/EU:	Yes