

# High-Intensity LED in Plastic T-1<sup>3/4</sup> Package



## OVLGx0CyB9 Series

### Features:

- Narrow beam angle
- High brightness LED
- Water clear plastic package
- UV resistant epoxy




### Description:

Each device in the **OVLG Series** is a high intensity LED mounted in a clear plastic T-1<sup>3/4</sup> package. Each device incorporates an integral molded lens that enables a narrow beam angle and provides an even emission pattern. Designed to produce light over a wide range of drive currents, these LEDs are useful in applications that require a higher on-axis brightness than that achievable with standard lamps.

### Applications:

- Indoor/outdoor applications
- Variable message boards
- Store front signage
- Indicators

| Part Number | Material | Emitted Color | Intensity Typ. mcd | Lens Color |
|-------------|----------|---------------|--------------------|------------|
| OVLGB0C6B9  | InGaN    | Blue          | 7,200              | Clear      |
| OVLGC0C6B9  |          | Blue-Green    | 23,000             |            |
| OVLGS0C8B9  | AlInGaP  | Red           | 14,000             |            |
| OVLGY0C9B9  |          | Yellow        | 14,000             |            |



1 ANODE 2 CATHODE  
DIMENSIONS ARE IN INCHES [MM]

**DO NOT LOOK DIRECTLY  
AT LED WITH  
UNSHIELDED EYES OR  
DAMAGE TO RETINA MAY  
OCCUR.**



RoHS



### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# High-Intensity LED in Plastic T-1<sup>3/4</sup> Package



## OVLGx0CyB9 Series

### Electrical Specifications

**Absolute Maximum Ratings** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

|  |                    |             |
|--|--------------------|-------------|
| Storage Temperature Range  | -40 ~ +100 °C      |             |
| Operating Temperature Range  | -40 ~ +100 °C      |             |
| Reverse Voltage  | 5 V                |             |
| Continuous Forward Current   | Blue, Blue-Green   | 25 mA       |
|  | Red, Yellow        | 50 mA       |
| Peak Forward Current (10% Duty Cycle, 1 kHz)                                   | 100 mA             |             |
| Power Dissipation  | Blue, Blue-Green   | 100 mW      |
|  | Red, Yellow        | 120 mW      |
| Current Linearity vs Ambient Temperature                                       | Blue, Blue-Green   | -0.29 mA/°C |
|  | Red, Yellow        | -0.72 mA/°C |
| LED Junction Temperature   | 125° C             |             |
| Electrostatic Discharge Classification (JEDEC-JESD22-A114F)                    | Class 1C           |             |
| Lead Soldering Temperature (3 mm from the base of the epoxy bulb) <sup>1</sup> | 260° C / 5 seconds |             |

**Electrical Characteristics** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| SYMBOL                      | PARAMETER           | COLOR      | MIN    | TYP    | MAX  | UNITS         | CONDITIONS           |
|-----------------------------|---------------------|------------|--------|--------|------|---------------|----------------------|
| $I_V$                       | Luminous Intensity  | Blue       | 4,360  | 7,200  | ---- | mcd           | $I_F = 20\text{ mA}$ |
|                             |                     | Blue-Green | 11,970 | 23,000 | ---- |               |                      |
|                             |                     | Red        | 8,550  | 14,000 | ---- |               |                      |
|                             |                     | Yellow     | 8,550  | 14,000 | ---- |               |                      |
| $V_F$                       | Forward Voltage     | Blue       | 2.6    | 3.2    | 4.0  | V             | $I_F = 20\text{ mA}$ |
|                             |                     | Blue-Green |        |        |      |               |                      |
|                             |                     | Red        | 1.8    | 2.0    | 2.4  |               |                      |
|                             |                     | Yellow     |        |        |      |               |                      |
| $I_R$                       | Reverse Current     | Blue       | ----   | ----   | 10   | $\mu\text{A}$ | $V_R = 5\text{ V}$   |
|                             |                     | Blue-Green |        |        |      |               |                      |
|                             |                     | Red        |        |        |      |               |                      |
|                             |                     | Yellow     |        |        |      |               |                      |
| $\lambda_D$                 | Dominant Wavelength | Blue       | 460    | 470    | 475  | nm            | $I_F = 20\text{ mA}$ |
|                             |                     | Blue-Green | 499    | 505    | 511  |               |                      |
|                             |                     | Red        | 620    | 623    | 630  |               |                      |
|                             |                     | Yellow     | 585    | 589    | 595  |               |                      |
| 2 $\theta_{\frac{1}{2}}$ -H | 50% Power Angle     | Blue       | ----   | 15     | ---- | deg           | $I_F = 20\text{ mA}$ |
|                             |                     | Blue-Green | ----   | 15     | ---- |               |                      |
|                             |                     | Red        | ----   | 8      | ---- |               |                      |
|                             |                     | Yellow     | ----   | 8      | ---- |               |                      |

**General Note**

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# High-Intensity LED in Plastic T-1<sup>3/4</sup> Package



## OVLGx0CyB9 Series

### Typical Electro-Optical Characteristics Curves—Blue & Blue-Green




Fig.1 Forward Current vs. Forward Voltage




Fig.2 Luminous Intensity vs. Forward Current




Fig.3 Reverse Current vs. Reverse Voltage




Fig.4 Allowable Forward Current vs. Ambient Temperature




Fig.5 Luminous Intensity at  $I_f=20mA$  vs. Ambient Temperature




Fig.1 Forward Current vs. Forward Voltage




Fig.2 Luminous Intensity vs. Forward Current




Fig.3 Reverse Current vs. Reverse Voltage




Fig.4 Allowable Forward Current vs. Ambient Temperature

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# High-Intensity LED in Plastic T-1<sup>3/4</sup> Package



## OVLGx0CyB9 Series

### Typical Electro-Optical Characteristics Curves—Red & Yellow




Fig.1 Forward Current vs. Forward Voltage




Fig.2 Luminous Intensity vs. Forward Current




Fig.3 Reverse Current vs. Reverse Voltage




Fig.4 Allowable Forward Current vs. Ambient Temperature




Fig.5 Luminous Intensity at I<sub>F</sub> = 20mA vs. Ambient Temperature




Fig.1 Forward Current vs. Forward Voltage




Fig.2 Luminous Intensity vs. Forward Current




Fig.3 Reverse Current vs. Reverse Voltage




Fig.4 Allowable Forward Current vs. Ambient Temperature

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# High-Intensity LED in Plastic T-1 $\frac{3}{4}$ Package


## OVLGx0CyB9 Series



Beam Angle:



**Packaging:** 500 pcs per anti-static bag with desiccant



# High-Intensity LED in Plastic T-1<sup>3/4</sup> Package



## OVLGx0CyB9 Series

### Reliability Test

LED lamps are checked by reliability tests based on MIL standards.

#### 1. Test Conditions, Acceptable Criteria & Results

| Classification     | Test Item                        | Std. Test Method           | Test Conditions                                      | Duration   | Unit | Acc / Rej Criteria | Result |
|--------------------|----------------------------------|----------------------------|--|------------|------|--------------------|--------|
| Life Test          | Operation Life Test (OLT)        | MIL-STD-750D Method 1026.3 | T <sub>A</sub> =25°C, I <sub>F</sub> =30mA *         | 1000 Hrs   | 100  | 0 / 1              | Pass   |
| Environmental Test | High Temperature Storage (HTS)   | MIL-STD-750D Method 1032.1 | T <sub>A</sub> =100°C                                | 1000 Hrs   | 100  | 0 / 1              | Pass   |
|                    | Low Temperature Storage (LTS)    | MIL-STD-750D Method 1032.1 | T <sub>A</sub> =-40°C                                | 1000 Hrs   | 100  | 0 / 1              | Pass   |
|                    | Temp. & Humidity with Bias (THB) | MIL-STD-750D Method 103B   | T <sub>A</sub> =85°C, Rh=85%<br>I <sub>F</sub> =20mA | 500 Hrs    | 100  | 0 / 1              | Pass   |
|                    | Thermal Shock Test (TST)         | MIL-STD-750D Method 1056.1 | 0°C ~ 100°C<br>2min 2min                             | 100 cycles | 100  | 0 / 1              | Pass   |
|                    | Temperature Cycling Test (TCT)   | MIL-STD-750D Method 1051.5 | -40°C ~ 25°C ~ 100°C ~ 25°C<br>30min 5min 30min 5min | 100 cycles | 100  | 0 / 1              | Pass   |
| Mechanical Test    | Solderability                    | MIL-STD-750D Method 2026.4 | 235±5°C, 5 sec.                                      | 1 time     | 20   | 0 / 1              | Pass   |
|                    | Resistance to Soldering Heat     | MIL-STD-750D Method 2031.1 | 260±5°C, 5 sec.                                      | 1 time     | 20   | 0 / 1              | Pass   |
|                    | Lead Integrity                   | MIL-STD-750D Method 2036.3 | Load 2.5N (0.25kgf)<br>0°~90°~0°, bend               | 3 times    | 20   | 0 / 1              | Pass   |

Remark: ( \*) I<sub>F</sub> = 30mA for AllnGaP chip; I<sub>F</sub> = 20mA for InGan chip  
( \*\*) I<sub>F</sub> = 20mA for AllnGaP chip; I<sub>F</sub> = 10mA for InGan chip

#### 2. Failure Criteria (T<sub>A</sub> = 25°C):

| Test Item          | Symbol         | Test Conditions       | Criteria for Judgment |           |
|--------------------|----------------|-----------------------|-----------------------|-----------|
|                    |                |                       | Min.                  | Max       |
| Luminous Intensity | I <sub>V</sub> | I <sub>F</sub> = 20mA | LSLx0.7 **            |           |
| Forward Voltage    | V <sub>F</sub> | I <sub>F</sub> = 20mA |                       | USLx1.1 * |

( \*) USL: Upper Standard Level, ( \*\*) LSL: Lower Standard Level

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com