

Metallized Polypropylen (PP) Filter Capacitors in PCM 27.5 mm to 52.5 mm. Capacitances from 0.68 μF to 75 μF . Rate Voltages from 230 VAC to 440 VAC.

Special Features

- High volume/capacitance ratio
- High peak current capabilities
- Self-healing
- Long lifetime
- AEC-Q200 qualified
- According to RoHS 2011/65/EU

Typical Applications


- For high frequency applications e.g.
- AC filtering in UPS systems
 - Harmonic filter
 - Welding equipment
 - Renewable energy - grid interface

Construction

Dielectric:
Polypropylene (PP) film

Capacitor electrodes:
Vacuum-deposited

Internal construction:



Encapsulation:
Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

Terminations:
Tinned wire.

Marking:
Colour: Red. Marking: Black.

Electrical Data

Capacitance range:
0.68 μF to 75 μF

Rated voltages: 230 VAC, 275 VAC, 305 VAC, 350 VAC, 440 VAC

Capacitance tolerances:
 $\pm 20\%$, $\pm 10\%$, $\pm 5\%$

Operating temperature range:
 -55°C to $+105^\circ\text{C}$

Climatic test category:
55/105/56 in accordance with IEC

Insulation resistance at $+20^\circ\text{C}$:
 $\geq 30\,000$ sec ($\text{M}\Omega \times \mu\text{F}$)
Measuring voltage: 100 V/1 min.

Test voltage:
 $1.5 U_{rDC}$, 10sec.

Test specifications:
In accordance with IEC 61071 and 60068

Dissipation factors at $+20^\circ\text{C}$: $\tan \delta$

| at f | PCM 27.5 | PCM 37.5 | PCM 52.5 |
|--------|--------------------------|--------------------------|--------------------------|
| 1 kHz | $\leq 5 \times 10^{-4}$ | $\leq 10 \times 10^{-4}$ | $\leq 15 \times 10^{-4}$ |
| 10 kHz | $\leq 20 \times 10^{-4}$ | $\leq 45 \times 10^{-4}$ | $\leq 90 \times 10^{-4}$ |

Reference frequency 1 kHz in accordance with IEC 60384-1

Maximum pulse rise time:

| PCM | max. pulse rise time V/ μsec at $T_A < 40^\circ\text{C}$ | | | | |
|------|---|---------|---------|---------|---------|
| | 230 VAC | 275 VAC | 305 VAC | 350 VAC | 440 VAC |
| 27.5 | 45 | 55 | 68 | 100 | 110 |
| 37.5 | 20 | 30 | 35 | 50 | 70 |
| 52.5 | 10 | 13 | 15 | 25 | 40 |

for pulses equal to the rated voltage (U_{rDC})

Mechanical Tests

Pull test on pins:
10 N in direction of pins according to IEC 60068-2-21


Vibration:
6 hours at 10...2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

Low air density:
1kPa = 10 mbar in accordance with IEC 60068-2-13

Bump test:
4000 bumps at 390 m/sec^2 in accordance with IEC 60068-2-29

Voltage derating:

A voltage derating factor must be applied according to the graph:



Reliability:

Operational life > 60000 hours at U_r
Failure rate < 10 fit ($0.5 \times U_r$ and 40°C)

Packing

Available taped and reeled up to and including case size 15 x 26 x 31.5 / PCM 27.5 mm.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

Continuation

General Data

| Capacitance | W | H | L | PCM** | Pin | 230 VAC*/450 VDC | | Part number |
|-------------|----|------|------|-------|-----|---------------------|---|-------------------|
| | | | | | | I _s A | I _{rms} (10 kHz) at 85° C A | |
| 1.0 μF | 9 | 19 | 31.5 | 27.5 | 2 | 45 | 2.5 | MKPF3Y41006A_____ |
| 1.5 " | 11 | 21 | 31.5 | 27.5 | 2/4 | 70 | 3 | MKPF3Y41506B_____ |
| 2.2 " | 11 | 21 | 31.5 | 27.5 | 2/4 | 100 | 3.5 | MKPF3Y42206B_____ |
| 3.3 " | 13 | 24 | 31.5 | 27.5 | 2/4 | 150 | 5 | MKPF3Y43306D_____ |
| 4.7 " | 15 | 26 | 31.5 | 27.5 | 2/4 | 210 | 7.5 | MKPF3Y44706F_____ |
| 6.8 " | 17 | 29 | 31.5 | 27.5 | 2/4 | 300 | 8.5 | MKPF3Y46806G_____ |
| 10 μF | 20 | 39.5 | 31.5 | 27.5 | 2/4 | 450 | 11.5 | MKPF3Y51006J_____ |
| | 19 | 32 | 41.5 | 37.5 | 2/4 | 200 | 8 | MKPF3Y51007F_____ |
| 12 " | 19 | 32 | 41.5 | 37.5 | 2/4 | 240 | 10 | MKPF3Y51207F_____ |
| 15 " | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 300 | 12 | MKPF3Y51507G_____ |
| 20 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 400 | 14 | MKPF3Y52007H_____ |
| 22 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 440 | 15 | MKPF3Y52207H_____ |
| 25 " | 31 | 46 | 41.5 | 37.5 | 2/4 | 500 | 17 | MKPF3Y52507I_____ |
| 30 " | 31 | 46 | 41.5 | 37.5 | 2/4 | 600 | 19 | MKPF3Y53007I_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 300 | 15 | MKPF3Y53009D_____ |
| 35 " | 35 | 50 | 41.5 | 37.5 | 2/4 | 700 | 20.5 | MKPF3Y53507J_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 350 | 15 | MKPF3Y53509D_____ |
| 40 " | 30 | 45 | 57 | 52.5 | 2/4 | 400 | 17.5 | MKPF3Y54009E_____ |
| 45 " | 30 | 45 | 57 | 52.5 | 2/4 | 450 | 18.5 | MKPF3Y54509E_____ |
| 50 " | 35 | 50 | 57 | 52.5 | 4 | 500 | 21 | MKPF3Y55009F_____ |
| 55 " | 35 | 50 | 57 | 52.5 | 4 | 550 | 22 | MKPF3Y55509F_____ |
| 60 " | 45 | 55 | 57 | 52.5 | 4 | 600 | 23 | MKPF3Y56009H_____ |
| 65 " | 45 | 55 | 57 | 52.5 | 4 | 650 | 25.5 | MKPF3Y56509H_____ |
| 70 " | 45 | 55 | 57 | 52.5 | 4 | 700 | 26 | MKPF3Y57009H_____ |
| 75 " | 45 | 65 | 57 | 52.5 | 4 | 750 | 27 | MKPF3Y57509J_____ |


* AC voltages: $f \leq 100$ Hz

** PCM = Printed circuit module = pin spacing


Dims. in mm.

| Part number completion: | |
|-----------------------------|------------|
| Version code: | 2-pin = 00 |
| | 4-pin = D4 |
| Tolerance: | 20 % = M |
| | 10 % = K |
| | 5 % = J |
| Packing: | bulk = S |
| Pin length: | 6-2 = SD |
| Taped version see page 161. | |

2-pin version



4-pin version



Rights reserved to amend design data without prior notification.

Continuation page 109

Continuation

General Data

| Capacitance | W | H | L | PCM** | Pin | 275 VAC*/600 VDC | | Part number |
|-------------|----|------|------|-------|-----|---------------------|---|-------------------|
| | | | | | | I _s A | I _{rms} (10 kHz) at 85° C A | |
| 1.0 μF | 9 | 19 | 31.5 | 27.5 | 2 | 55 | 2.5 | MKPF1W41006A_____ |
| 1.5 " | 11 | 21 | 31.5 | 27.5 | 2/4 | 80 | 3.5 | MKPF1W41506B_____ |
| 2.2 " | 13 | 24 | 31.5 | 27.5 | 2/4 | 120 | 5 | MKPF1W42206D_____ |
| 3.3 " | 15 | 26 | 31.5 | 27.5 | 2/4 | 180 | 5.5 | MKPF1W43306F_____ |
| 4.7 " | 17 | 34.5 | 31.5 | 27.5 | 2/4 | 260 | 8 | MKPF1W44706I_____ |
| 6.8 " | 20 | 39.5 | 31.5 | 27.5 | 2/4 | 370 | 10 | MKPF1W46806J_____ |
| 10 μF | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 300 | 10 | MKPF1W51007G_____ |
| 12 " | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 360 | 12 | MKPF1W51207G_____ |
| 15 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 450 | 14 | MKPF1W51507H_____ |
| 20 " | 25 | 45 | 57 | 52.5 | 2/4 | 195 | 11 | MKPF1W51509D_____ |
| | 31 | 46 | 41.5 | 37.5 | 2/4 | 600 | 16 | MKPF1W52007I_____ |
| 22 " | 25 | 45 | 57 | 52.5 | 2/4 | 260 | 12 | MKPF1W52009D_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 286 | 14 | MKPF1W52209D_____ |
| 25 " | 30 | 45 | 57 | 52.5 | 2/4 | 325 | 16 | MKPF1W52509E_____ |
| 30 " | 35 | 50 | 57 | 52.5 | 4 | 390 | 17 | MKPF1W53009F_____ |
| 35 " | 35 | 50 | 57 | 52.5 | 4 | 455 | 20 | MKPF1W53509F_____ |
| 40 " | 45 | 55 | 57 | 52.5 | 4 | 520 | 21 | MKPF1W54009H_____ |
| 45 " | 45 | 55 | 57 | 52.5 | 4 | 585 | 23 | MKPF1W54509H_____ |
| 50 " | 45 | 65 | 57 | 52.5 | 4 | 650 | 24 | MKPF1W55009J_____ |


* AC voltages: $f \leq 100$ Hz

** PCM = Printed circuit module = pin spacing


Dims. in mm.

| Part number completion: | |
|-----------------------------|---------------------------------|
| Version code: | 2-pin = 00 4-pin = D4 |
| Tolerance: | 20 % = M 10 % = K 5 % = J |
| Packing: | bulk = S |
| Pin length: | 6-2 = SD |
| Taped version see page 161. | |

2-pin version



4-pin version



Rights reserved to amend design data without prior notification.

Continuation page 110

Continuation

General Data

| Capacitance | W | H | L | PCM** | Pin | 305 VAC*/630 VDC | | Part number |
|--------------|----|------|------|-------|-----|------------------|----------------------------------|-------------------|
| | | | | | | I_s A | I_{rms} (10 kHz) at 85° C A | |
| 0.68 μ F | 9 | 19 | 31.5 | 27.5 | 2 | 50 | 2 | MKPFAW36806A_____ |
| 1.0 μ F | 11 | 21 | 31.5 | 27.5 | 2/4 | 68 | 3 | MKPFAW41006B_____ |
| 1.5 " | 13 | 24 | 31.5 | 27.5 | 2/4 | 110 | 4 | MKPFAW41506D_____ |
| 2.2 " | 15 | 26 | 31.5 | 27.5 | 2/4 | 150 | 5 | MKPFAW42206F_____ |
| 3.3 " | 17 | 29 | 31.5 | 27.5 | 2/4 | 220 | 7 | MKPFAW43306G_____ |
| 4.7 " | 20 | 39.5 | 31.5 | 27.5 | 2/4 | 320 | 9 | MKPFAW44706J_____ |
| 6.8 " | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 245 | 10 | MKPFAW46807G_____ |
| 10 μ F | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 350 | 12 | MKPFAW51007H_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 150 | 10 | MKPFAW51009D_____ |
| 12 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 420 | 13 | MKPFAW51207H_____ |
| 15 " | 31 | 46 | 41.5 | 37.5 | 2/4 | 525 | 15 | MKPFAW51507I_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 225 | 13 | MKPFAW51509D_____ |
| 20 " | 40 | 55 | 41.5 | 37.5 | 2/4 | 700 | 19 | MKPFAW52007K_____ |
| | 30 | 45 | 57 | 52.5 | 2/4 | 300 | 14 | MKPFAW52009E_____ |
| 22 " | 35 | 50 | 57 | 52.5 | 4 | 330 | 16 | MKPFAW52209F_____ |
| 25 " | 35 | 50 | 57 | 52.5 | 4 | 375 | 17 | MKPFAW52509F_____ |
| 30 " | 45 | 55 | 57 | 52.5 | 4 | 450 | 21 | MKPFAW53009H_____ |
| 35 " | 45 | 65 | 57 | 52.5 | 4 | 525 | 22 | MKPFAW53509J_____ |


* AC voltages: $f \leq 100$ Hz

** PCM = Printed circuit module = pin spacing


Dims. in mm.

| Part number completion: | |
|-----------------------------|---------------------------------|
| Version code: | 2-pin = 00 4-pin = D4 |
| Tolerance: | 20 % = M 10 % = K 5 % = J |
| Packing: | bulk = S |
| Pin length: | 6-2 = SD |
| Taped version see page 161. | |

2-pin version



4-pin version



Rights reserved to amend design data without prior notification.

Continuation page 111

Continuation

General Data

| Capacitance | W | H | L | PCM** | Pin | 350 VAC*/700 VDC | | Part number |
|-------------|----|------|------|-------|-----|---------------------|---|-------------------|
| | | | | | | I _s A | I _{rms} (10 kHz) at 85° C A | |
| 0.68 µF | 9 | 19 | 31.5 | 27.5 | 2 | 70 | 1.5 | MKPFBW36806A_____ |
| 1.0 µF | 11 | 21 | 31.5 | 27.5 | 2/4 | 100 | 3 | MKPFBW41006B_____ |
| 1.5 " | 13 | 24 | 31.5 | 27.5 | 2/4 | 150 | 4 | MKPFBW41506D_____ |
| 2.2 " | 15 | 26 | 31.5 | 27.5 | 2/4 | 220 | 5 | MKPFBW42206F_____ |
| 3.3 " | 17 | 29 | 31.5 | 27.5 | 2/4 | 330 | 7 | MKPFBW43306G_____ |
| 4.7 " | 20 | 39.5 | 31.5 | 27.5 | 2/4 | 470 | 11 | MKPFBW44706J_____ |
| 6.8 " | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 340 | 10 | MKPFBW46807G_____ |
| 10 µF | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 500 | 13 | MKPFBW51007H_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 250 | 11 | MKPFBW51009D_____ |
| 12 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 600 | 14 | MKPFBW51207H_____ |
| 15 " | 31 | 46 | 41.5 | 37.5 | 2/4 | 750 | 16 | MKPFBW51507I_____ |
| | 25 | 45 | 57 | 52.5 | 2/4 | 375 | 13 | MKPFBW51509D_____ |
| 20 " | 40 | 55 | 41.5 | 37.5 | 2/4 | 1000 | 18 | MKPFBW52007K_____ |
| | 30 | 45 | 57 | 52.5 | 2/4 | 500 | 16 | MKPFBW52009E_____ |
| 22 " | 35 | 50 | 57 | 52.5 | 4 | 550 | 18 | MKPFBW52209F_____ |
| 25 " | 35 | 50 | 57 | 52.5 | 4 | 625 | 19 | MKPFBW52509F_____ |
| 30 " | 45 | 55 | 57 | 52.5 | 4 | 750 | 22 | MKPFBW53009H_____ |
| 35 " | 45 | 65 | 57 | 52.5 | 4 | 870 | 25 | MKPFBW53509J_____ |

| Capacitance | W | H | L | PCM** | Pin | 440 VAC*/1000 VDC | | Part number |
|-------------|----|------|------|-------|-----|---------------------|---|-------------------|
| | | | | | | I _s A | I _{rms} (10 kHz) at 85° C A | |
| 0.68 " | 13 | 24 | 31.5 | 27.5 | 2/4 | 74.8 | 3 | MKPF4W36806D_____ |
| 1.0 µF | 13 | 24 | 31.5 | 27.5 | 2/4 | 110 | 4 | MKPF4W41006D_____ |
| 1.5 " | 17 | 29 | 31.5 | 27.5 | 2/4 | 165 | 5 | MKPF4W41506G_____ |
| 2.2 " | 20 | 39.5 | 31.5 | 27.5 | 2/4 | 240 | 6 | MKPF4W42206J_____ |
| 3.3 " | 20 | 39.5 | 41.5 | 37.5 | 2/4 | 230 | 7.5 | MKPF4W43307G_____ |
| 4.7 " | 24 | 45.5 | 41.5 | 37.5 | 2/4 | 330 | 8.5 | MKPF4W44707H_____ |
| 6.8 " | 31 | 46 | 41.5 | 37.5 | 2/4 | 480 | 11.5 | MKPF4W46807I_____ |
| 10 µF | 30 | 45 | 57 | 52.5 | 2/4 | 400 | 16 | MKPF4W51009E_____ |
| 12 " | 35 | 50 | 57 | 52.5 | 4 | 480 | 17 | MKPF4W51209F_____ |

* AC voltages: $f \leq 100$ Hz

** PCM = Printed circuit module = pin spacing

Dims. in mm.




| Part number completion: | |
|-----------------------------|---------------------------------|
| Version code: | 2-pin = 00 4-pin = D4 |
| Tolerance: | 20 % = M 10 % = K 5 % = J |
| Packing: | bulk = S |
| Pin length: | 6-2 = SD |
| Taped version see page 161. | |

Rights reserved to amend design data without prior notification.






Continuation page 112

Continuation






Impedance change with frequency
(general guide).



Permissible AC voltage in relation to frequency at 10° C internal temperature rise
(general guide).



Permissible AC current in relation to frequency at 10° C internal temperature rise
(general guide).



Recommendation for Processing and Application of Through-Hole Capacitors

Soldering Process

Internal temperature of the capacitor must be kept as follows:

Polyester: preheating: $T_{max.} \leq 125^{\circ}C$
soldering: $T_{max.} \leq 135^{\circ}C$

Polypropylene: preheating: $T_{max.} \leq 100^{\circ}C$
soldering: $T_{max.} \leq 110^{\circ}C$

Single wave soldering

Soldering bath temperature: $T < 260^{\circ}C$


Dwell time: $t < 5 \text{ sec}$

Double wave soldering

Soldering bath temperature: $T < 260^{\circ}C$

Dwell time: $\Sigma t < 5 \text{ sec}$

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.



WIMA Quality and Environmental Philosophy

ISO 9001:2015 Certification

ISO 9001:2015 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2015 of our factories by the infaz (Institut für Auditierung und Zertifizierung) certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- pin attachment
- cast resin preparation/encapsulation
- 100% final inspection
- Testing as per customer requirements

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- Lead
- PCB
- CFC
- Hydrocarbon chloride
- Chromium 6+
- PBB/PBDE
- Arsenic
- Cadmium
- Mercury
- etc.

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- adhesive tapes made of plastic
- metal clips

RoHS Compliance

According to the RoHS Directive 2011/65/EU as amended from time to time certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2011/65/EU

WIMA capacitors are lead free in accordance with RoHS 2011/65/EU

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2004

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2004 to optimize the production processes with regard to energy and resources.

Typical Dimensions for Taping Configuration




Diagram 1:
PCM 2.5/5/7.5mm

Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm

*PCM 27.5 taping possible with two feed holes between components

| Designation | Symbol | Dimensions for Radial Taping | | | | | | |
|--|-----------------------|--|--|---|---|---|---|---|
| | | PCM 2.5 taping | PCM 5 taping | PCM 7.5 taping | PCM 10 taping* | PCM 15 taping* | PCM 22.5 taping | PCM 27.5 taping |
| Carrier tape width | W | 18.0 ±0.5 | 18.0 ±0.5 | 18.0 ±0.5 | 18.0 ±0.5 | 18.0 ±0.5 | 18.0 ±0.5 | 18.0 ±0.5 |
| Hold-down tape width | W ₀ | 6.0 for hot-sealing adhesive tape | 6.0 for hot-sealing adhesive tape | 12.0 for hot-sealing adhesive tape | 12.0 for hot-sealing adhesive tape | 12.0 for hot-sealing adhesive tape | 12.0 for hot-sealing adhesive tape | 12.0 for hot-sealing adhesive tape |
| Hole position | W ₁ | 9.0 ±0.5 | 9.0 ±0.5 | 9.0 ±0.5 | 9.0 ±0.5 | 9.0 ±0.5 | 9.0 ±0.5 | 9.0 ±0.5 |
| Hold-down tape position | W ₂ | 0.5 to 3.0 max. | 0.5 to 3.0 max. | 0.5 to 3.0 max. | 0.5 to 3.0 max. | 0.5 to 3.0 max. | 0.5 to 3.0 max. | 0.5 to 3.0 max. |
| Feed hole diameter | D ₀ | 4.0 ±0.2 | 4.0 ±0.2 | 4.0 ±0.2 | 4.0 ±0.2 | 4.0 ±0.2 | 4.0 ±0.2 | 4.0 ±0.2 |
| Pitch of component | P | 12.7 ±1.0 | 12.7 ±1.0 | 12.7 ±1.0 | 25.4 ±1.0 | 25.4 ±1.0 | 38.1 ±1.5 | 38.1 ±1.5 or 50.8 ±1.5 |
| Feed hole pitch | P ₀ | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch | 12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch |
| Feed hole centre to pin | P ₁ | 5.1 ±0.5 | 3.85 ±0.7 | 2.6 ±0.7 | 7.7 ±0.7 | 5.2 ±0.7 | 7.8 ±0.7 | 5.3 ±0.7 |
| Hole centre to component centre | P ₂ | 6.35 ±1.3 | 6.35 ±1.3 | 6.35 ±1.3 | 12.7 ±1.3 | 12.7 ±1.3 | 19.05 ±1.3 | 19.05 ±1.3 |
| Feed hole centre to bottom edge of the component | H | 16.5 ±0.3 18.5 ±0.5 | 16.5 ±0.3 18.5 ±0.5 | 16.5 ±0.5 18.5 ±0.5 | 16.5 ±0.5 18.5 ±0.5 | 16.5 ±0.5 18.5 ±0.5 | 16.5 ±0.5 18.5 ±0.5 | 16.5 ±0.5 18.5 ±0.5 |
| Feed hole centre to top edge of the component | H ₁ | H+H _{component} < H ₁ 32.25 max. | H+H _{component} < H ₁ 32.25 max. | H+H _{component} < H ₁ 24.5 to 31.5 | H+H _{component} < H ₁ 25.0 to 31.5 | H+H _{component} < H ₁ 26.0 to 37.0 | H+H _{component} < H ₁ 30.0 to 43.0 | H+H _{component} < H ₁ 35.0 to 45.0 |
| Pin spacing at upper edge of carrier tape | F | 2.5 ±0.5 | 5.0 ^{+0.8} _{-0.2} | 7.5 ±0.8 | 10.0 ±0.8 | 15 ±0.8 | 22.5 ±0.8 | 27.5 ±0.8 |
| Pin diameter | d | 0.4 ±0.05 | 0.5 ±0.05 | 0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05} | 0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05} | 0.8 ^{+0.08} _{-0.05} | 0.8 ^{+0.08} _{-0.05} | 0.8 ^{+0.08} _{-0.05} |
| Component alignment | Δh | ± 2.0 max. | ± 2.0 max. | ± 3.0 max. | ± 3.0 max. | ± 3.0 max. | ± 3.0 max. | ± 3.0 max. |
| Total tape thickness | t | 0.6 ±0.2 | 0.6 ±0.2 | 0.6 ±0.2 | 0.6 ±0.2 | 0.6 ±0.2 | 0.6 ±0.2 | 0.6 ±0.2 |
| Package (see also page 162) | ROLL/AMMO | | | AMMO | | | | |
| | REEL | φ 360 max. φ 30 ±1 | B 52 ±2 58 ±2 } depending on comp. dimensions | REEL | φ 360 max. φ 30 ±1 | 52 ±2 58 ±2 or 66 ±2 | REEL | φ 500 max. φ 25 ±1 |
| Unit | see details page 163. | | | | | | | |

Dims in mm.

* Diameter of pins see General Data.


* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 11). P₀ = 12.7 or 15.0 is possible


Please clarify customer-specific deviations with the manufacturer.

Types of Tape Packaging of Capacitors for Automatic Radial Insertion


■ ROLL Packaging



■ AMMO Packaging



■ REEL Packaging



BAR CODE (Labelling)

Labelling of package units in plain text and with alphanumerical Bar Code

- WIMA supplier number
- Date code
- Customer's P/O number
- P/O line
- Customer's part number
- WIMA part number
- Quantity
- WIMA confirmation number
- Country of origin
- Customer name
- Handling unit number
- Week of delivery.

In addition part description of

- article
- capacitance value
- rated voltage
- dimensions
- technical note
- capacitance tolerance
- packing
- connecting information

BARCODE PDF417
BARCODE 2D Datamatrix

| | |
|--|--------------------------|
| WIMA Best Capacitors Made in Germany | |
| Werk Aurich | |
| Supplier-ID: LIEF.NR. | Date Code: 20210419 |
| | |
| Purchase Order No. (P/O): Bestellung xyz | P/O line: 100 |
| | |
| Customer Part No.: KUNDENTEILENUMMER | |
| | |
| WIMA Part No.: MKP1F041006B00KSSD | Quantity: 459 |
| | |
| WIMA Confirmation No.: 0001105072000100 | |
| | |
| Customer No.: 0000100002 | RoHS 2011/65/EU |
| Gross Weight [g]: 4557 | COO: DE |
| | |
| WIMA - MKP 10 WIMA Part No.: MKP1F041006B00KSSD MKP 10 1.0 µF 250 VDC 11x21x31.5 RM27.5 Standard 10% Lose - Standard Drähte 6-2 Vorlage Debitor Inland | |
| | 0001105072000100 |
| 1002021443 | QTY: 459 Week 19/2021 |

Packing Quantities for Capacitors with Radial Pins in PCM 2.5 mm to 22.5 mm



| PCM | Size | | | | bulk | pcs. per packing unit | | | | | | | | |
|----------------|------|------|-----------|-----------|------|-----------------------|-------|-------|-------|-------|-----------|-----------|-----|------|
| | | | | | | ROLL | | REEL | | | | AMMO | | |
| | W | H | L | Codes | | S | H16.5 | H18.5 | ø 360 | ø 500 | 340 x 340 | 490 x 370 | | |
| | | | | | N | O | F | I | H | J | A | C | B | D |
| 2.5 mm | 2.5 | 7 | 4.6 | 0B | 5000 | | 2200 | 2500 | | | | 2800 | | |
| | 3 | 7.5 | 4.6 | 0C | 5000 | | 2000 | 2300 | | | | 2300 | | |
| | 3.8 | 8.5 | 4.6 | 0D | 5000 | | 1500 | 1800 | | | | 1800 | | |
| | 4.6 | 9 | 4.6 | 0E | 5000 | | 1200 | 1500 | | | | 1500 | | |
| | 5.5 | 10 | 4.6 | 0F | 5000 | | 900 | 1200 | | | | 1200 | | |
| 5 mm | 2.5 | 6.5 | 7.2 | 1A | 5000 | | 2200 | 2500 | | | | 2800 | | |
| | 3 | 7.5 | 7.2 | 1B | 5000 | | 2000 | 2300 | | | | 2300 | | |
| | 3.5 | 8.5 | 7.2 | 1C | 5000 | | 1600 | 2000 | | | | 2000 | | |
| | 4.5 | 6 | 7.2 | 1D | 6000 | | 1300 | 1500 | | | | 1500 | | |
| | 4.5 | 9.5 | 7.2 | 1E | 4000 | | 1300 | 1500 | | | | 1500 | | |
| | 5 | 10 | 7.2 | 1F | 3500 | | 1100 | 1400 | | | | 1400 | | |
| | 5.5 | 7 | 7.2 | 1G | 4000 | | 1000 | 1200 | | | | 1200 | | |
| | 5.5 | 11.5 | 7.2 | 1H | 2500 | | 1000 | 1200 | | | | 1200 | | |
| | 6.5 | 8 | 7.2 | 1I | 2500 | | 800 | 1000 | | | | 1000 | | |
| | 7.2 | 8.5 | 7.2 | 1J | 2500 | | 700 | 1000 | | | | 1000 | | |
| | 7.2 | 13 | 7.2 | 1K | 2000 | | 700 | 950 | | | | 1000 | | |
| 8.5 | 10 | 7.2 | 1L | 2000 | | 600 | 800 | | | | 800 | | | |
| 8.5 | 14 | 7.2 | 1M | 1500 | | 600 | 800 | | | | 800 | | | |
| 11 | 16 | 7.2 | 1N | 1000 | | 500 | 600 | | | | 640 | | | |
| 7.5 mm | 2.5 | 7 | 10 | 2A | 5000 | | | 2500 | 4400 | | | 2500 | | |
| | 3 | 8.5 | 10 | 2B | 5000 | | | 2200 | 4300 | | | 2300 | | 4150 |
| | 4 | 9 | 10 | 2C | 4000 | | | 1700 | 3200 | | | 1700 | | 3000 |
| | 4.5 | 9.5 | 10.3 | 2D | 3500 | | | 1500 | 2900 | | | 1400 | | 2700 |
| | 5 | 10.5 | 10.3 | 2E | 3000 | | | 1300 | 2500 | | | 1300 | | |
| | 5.7 | 12.5 | 10.3 | 2F | 2000 | | | 1000 | 2200 | | | 1100 | | |
| | 7.2 | 12.5 | 10.3 | 2G | 1500 | | | 900 | 1800 | | | 1000 | | |
| 10 mm | 3 | 9 | 13 | 3A | 3000 | | | 1100 | 2200 | | | | | 1900 |
| | 4 | 8.5 | 13.5 | FA | 3000 | | | 900 | 1600 | | | | | 1450 |
| | 4 | 9 | 13 | 3C | 3000 | | | 900 | 1600 | | | | | 1450 |
| | 4 | 9.5 | 13 | 3D | 3000 | | | 900 | 1600 | | | | | 1400 |
| | 5 | 10 | 13.5 | FB | 2000 | | | 700 | 1300 | | | | | 1200 |
| | 5 | 11 | 13 | 3F | 3000 | | | 700 | 1300 | | | | | 1100 |
| | 6 | 12 | 13 | 3G | 2400 | | | 550 | 1100 | | | | | 1000 |
| | 6 | 12.5 | 13 | 3H | 2400 | | | 550 | 1100 | | | | | 1000 |
| 8 | 12 | 13 | 3I | 2000 | | | 400 | 800 | | | | | 740 | |
| 15 mm | 5 | 11 | 18 | 4B | 2400 | | | 600 | 1200 | | | | | 1150 |
| | 5 | 13 | 19 | FC | 1000 | | | 600 | 1200 | | | | | 1200 |
| | 6 | 12.5 | 18 | 4C | 2000 | | | 500 | 1000 | | | | | 1000 |
| | 6 | 14 | 19 | FD | 1000 | | | 500 | 1000 | | | | | 1000 |
| | 7 | 14 | 18 | 4D | 1600 | | | 450 | 900 | | | | | 850 |
| | 7 | 15 | 19 | FE | 1000 | | | 450 | 900 | | | | | 850 |
| | 8 | 15 | 18 | 4F | 1200 | | | 400 | 800 | | | | | 740 |
| | 8 | 17 | 19 | FF | 500 | | | 400 | 800 | | | | | 740 |
| | 9 | 14 | 18 | 4H | 1200 | | | 350 | 700 | | | | | 650 |
| | 9 | 16 | 18 | 4J | 900 | | | 350 | 700 | | | | | 650 |
| 10 | 18 | 19 | FG | 500 | | | 300 | 650 | | | | | 590 | |
| 11 | 14 | 18 | 4M | 1000 | | | 300 | 600 | | | | | 540 | |
| 22.5 mm | 5 | 14 | 26.5 | 5A | 1200 | | | | 800 | | | | | 770 |
| | 6 | 15 | 26.5 | 5B | 1000 | | | | 700 | | | | | 640 |
| | 7 | 16.5 | 26.5 | 5D | 760 | | | | 600 | | | | | 550 |
| | 8 | 20 | 28 | FH | 500 | | | | 500 | | | | | 480 |
| | 8.5 | 18.5 | 26.5 | 5F | 500 | | | | 480 | | | | | 450 |
| | 10 | 22 | 28 | FI | 570* | | | | 420 | | | | | 380 |
| | 10.5 | 19 | 26.5 | 5G | 594* | | | | 400 | | | | | 360 |
| | 10.5 | 20.5 | 26.5 | 5H | 594* | | | | 400 | | | | | 360 |
| | 11 | 21 | 26.5 | 5I | 561* | | | | 380 | | | | | 350 |
| | 12 | 24 | 28 | FJ | 480* | | | | 350 | | | | | 310 |

* TPS (Tray-Packing-System). Plate versions may have different packing units. Samples and pre-production needs on request.

■ Moulded versions.

Rights reserved to amend design data without prior notification.



Packing Quantities for Capacitors with Radial Pins in PCM 27.5 mm to 52.5 mm

| PCM | Size | | | | bulk | pcs. per packing unit | | | | | | | | | | | | |
|----------------|------|------|-----------|-----------|------|-----------------------|---|-------|-------|----------|-------|-------|-----------|-------|-----------|-------|-------|---|
| | | | | | | ROLL | | REEL | | | | AMMO | | | | | | |
| | W | H | L | Codes | | S | N | O | ø 360 | | ø 500 | | 340 x 340 | | 490 x 370 | | | |
| | | | | | | | | H16.5 | H18.5 | H16.5 | H18.5 | H16.5 | H18.5 | H16.5 | H18.5 | H16.5 | H18.5 | |
| | | | | | | | | F | I | H | J | A | C | B | D | | | |
| 27.5 mm | 9 | 19 | 31.5 | 6A | 567* | - | - | - | - | 460/340* | - | - | - | - | - | - | - | |
| | 11 | 21 | 31.5 | 6B | 459* | - | - | - | - | 380/280* | - | - | - | - | - | - | - | |
| | 13 | 24 | 31.5 | 6D | 378* | - | - | - | - | 300 | - | - | - | - | - | - | - | |
| | 13 | 25 | 33 | 6K | 405* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 15 | 26 | 31.5 | 6F | 324* | - | - | - | - | 270 | - | - | - | - | - | - | - | |
| | 15 | 26 | 33 | 6L | 324* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 17 | 29 | 31.5 | 6G | 198* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 17 | 34.5 | 31.5 | 6I | 198* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 20 | 32 | 33 | 6M | 162* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 20 | 39.5 | 31.5 | 6J | 162* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 37.5 mm | 9 | 19 | 41.5 | 7A | 441* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 11 | 22 | 41.5 | 7B | 357* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 13 | 24 | 41.5 | 7C | 294* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 15 | 26 | 41.5 | 7D | 252* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 17 | 29 | 41.5 | 7E | 154* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 19 | 32 | 41.5 | 7F | 140* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 20 | 39.5 | 41.5 | 7G | 126* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 24 | 45.5 | 41.5 | 7H | 112* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 28 | 38 | 41.5 | 7L | 84* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 31 | 46 | 41.5 | 7I | 84* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| | 35 | 50 | 41.5 | 7J | 35* | - | - | - | - | - | - | - | - | - | - | - | - | - |
| 40 | 55 | 41.5 | 7K | 28* | - | - | - | - | - | - | - | - | - | - | - | - | - | |
| 48.5 mm | 19 | 31 | 56 | 8D | 120* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 23 | 34 | 56 | 8E | 80* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 27 | 37.5 | 56 | 8H | 84* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 33 | 48 | 56 | 8J | 25* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 37 | 54 | 56 | 8L | 25* | - | - | - | - | - | - | - | - | - | - | - | - | |
| 52.5 mm | 25 | 45 | 57 | 9D | 70* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 30 | 45 | 57 | 9E | 60* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 35 | 50 | 57 | 9F | 25* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 45 | 55 | 57 | 9H | 20* | - | - | - | - | - | - | - | - | - | - | - | - | |
| | 45 | 65 | 57 | 9J | 20* | - | - | - | - | - | - | - | - | - | - | - | - | |

* for 2-inch transport pitches.

* TPS (Tray-Packing-System). Plate versions may have different packing units. Samples and pre-production needs on request.

■ Moulded versions. Rights reserved to amend design data without prior notification.

Updated data on www.wima.com



A WIMA part number consists of 18 digits and is composed as follows:

- Field 1 - 4: Type description
- Field 5 - 6: Rated voltage
- Field 7 - 10: Capacitance
- Field 11 - 12: Size and PCM
- Field 13 - 14: Version code (e.g. Snubber versions)
- Field 15: Capacitance tolerance
- Field 16: Packing
- Field 17 - 18: Pin length (untaped)

| | | | | | | | | | | | | | | | | | |
|----------|----------|----------|----------|----------|----------|----------|----------|----------|-------------|----------|----------|----------|----------|----------|----------|----------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 |
| M | K | S | 2 | C | 0 | 2 | 1 | 0 | 0 | 1 | A | 0 | 0 | M | S | S | D |
| MKS 2 | | | | 63 VDC | | 0.01 µF | | | 2.5x6.5x7.2 | | - | | 20% | bulk | 6 -2 | | |

| | | | | |
|---|---|---|---|---|
| <p>Type description:</p> <p>SMD-PET = SMDT SMD-PEN = SMDN SMD-PPS = SMDI FKP 02 = FKPO MKS 02 = MKS0 FKS 2 = FKS2 FKP 2 = FKP2 FKS 3 = FKS3 FKP 3 = FKP 3 MKS 2 = MKS2 MKP 2 = MKP2 MKS 4 = MKS4 MKP 4 = MKP4 MKP 10 = MKP1 FKP 4 = FKP4 FKP 1 = FKP1 MKP-X2 = MKX2 MKP-X1 R = MKX1 MKP-Y2 = MKY2 MP 3-X2 = MPX2 MP 3-X1 = MPX1 MP 3-Y2 = MPY2 MP 3R-Y2 = MPRY MKP 4F = MKPF Snubber MKP = SNMP Snubber FKP = SNFP GTO MKP = GTOM DC-LINK MKP 4 = DCP4 DC-LINK MKP 6 = DCP6 DC-LINK HC = DCHC</p> | <p>Rated voltage:</p> <p>50 VDC = B0 63 VDC = C0 100 VDC = D0 250 VDC = F0 400 VDC = G0 450 VDC = H0 520 VDC = H2 600 VDC = I0 630 VDC = J0 700 VDC = K0 800 VDC = L0 850 VDC = M0 900 VDC = N0 1000 VDC = O1 1100 VDC = P0 1200 VDC = Q0 1250 VDC = R0 1500 VDC = S0 1600 VDC = T0 1700 VDC = TA 2000 VDC = U0 2500 VDC = V0 3000 VDC = W0 4000 VDC = X0 6000 VDC = Y0 250 VAC = 0W 275 VAC = 1W 300 VAC = 2W 305 VAC = AW 350 VAC = BW 440 VAC = 4W 500 VAC = 5W ...</p> | <p>Capacitance:</p> <p>22 pF = 0022 47 pF = 0047 100 pF = 0100 150 pF = 0150 220 pF = 0220 330 pF = 0330 470 pF = 0470 680 pF = 0680 1000 pF = 1100 1500 pF = 1150 2200 pF = 1220 3300 pF = 1330 4700 pF = 1470 6800 pF = 1680 0.01 µF = 2100 0.022 µF = 2220 0.047 µF = 2470 0.1 µF = 3100 0.22 µF = 3220 0.47 µF = 3470 1 µF = 4100 2.2 µF = 4220 4.7 µF = 4470 10 µF = 5100 22 µF = 5220 47 µF = 5470 100 µF = 6100 220 µF = 6220 1000 µF = 7100 1500 µF = 7150 ...</p> | <p>Size:</p> <p>4.8x3.3x3 Size 1812 = KA 4.8x3.3x4 Size 1812 = KB 5.7x5.1x3.5 Size 2220 = QA 5.7x5.1x4.5 Size 2220 = QB 7.2x6.1x3 Size 2824 = TA 7.2x6.1x5 Size 2824 = TB 10.2x7.6x5 Size 4030 = VA 12.7x10.2x6 Size 5040 = XA 15.3x13.7x7 Size 6054 = YA 2.5x7x4.6 PCM 2.5 = 0B 3x7.5x4.6 PCM 2.5 = 0C 2.5x6.5x7.2 PCM 5 = 1A 3x7.5x7.2 PCM 5 = 1B 2.5x7x10 PCM 7.5 = 2A 3x8.5x10 PCM 7.5 = 2B 3x9x13 PCM 10 = 3A 4x9x13 PCM 10 = 3C 5x11x18 PCM 15 = 4B 6x12.5x18 PCM 15 = 4C 5x14x26.5 PCM 22.5 = 5A 6x15x26.5 PCM 22.5 = 5B 9x19x31.5 PCM 27.5 = 6A 11x21x31.5 PCM 27.5 = 6B 9x19x41.5 PCM 37.5 = 7A 11x22x41.5 PCM 37.5 = 7B 19x31x56 PCM 48.5 = 8D 25x45x57 PCM 52.5 = 9D ...</p> | <p>Tolerance:</p> <p>±20% = M ±10% = K ±5% = J ±2.5% = H ±1% = E ...</p> <p>Packing:</p> <p>AMMO H16.5 340x340 = A AMMO H16.5 490x370 = B AMMO H18.5 340x340 = C AMMO H18.5 490x370 = D REEL H16.5 360 = F REEL H16.5 500 = H REEL H18.5 360 = I REEL H18.5 500 = J ROLL H16.5 = N ROLL H18.5 = O BLISTER W12 180 = P BLISTER W12 330 = Q BLISTER W16 330 = R BLISTER W24 330 = T Bulk/TPS Standard = S ...</p> |
| | | | <p>Version code:</p> <p>Standard = 00 Version A1 = 1A Version A1.1.1 = 1B Version A2 = 2A ...</p> | <p>Pin length (untaped)</p> <p>3.5 ±0.5 = C9 6 -2 = SD 16 ±1 = P1 ...</p> <p>Pin length (taped)</p> <p>none = 00</p> |

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.