

## **Product information**

## 87 01 125

## **KNIPEX Cobra®**

**DIN ISO 8976** 



- push the button for adjustment on the workpiece: fast and comfortable handling
- fine adjustment: ensures optimum adjustment to differently sized workpieces and user-friendly handle position
- reliable catching of the hinge bolt: no unintentional shifting
- · box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx.
   61 HRC: high wear resistance and stable gripping
- one-hand adjustment
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- Chrome vanadium electric steel, forged, multi stage oil-hardened

Article No. 87 01 125  EAN 4003773069935  weight 90 g  Dimensions 125 x 78 x 14 mm	Allgemein	
weight 90 g	Article No.	87 01 125
	EAN	4003773069935
Dimensions 125 x 78 x 14 mm	weight	90 g
2 A TO A T T TIME	Dimensions	125 x 78 x 14 mm

Technische Attribute	
Adjustment positions	13
Capacities for nuts	1 Inch
Capacities for nuts	27 mm
Capacities for pipes (diameter)	Ø 27 mm

Klassifikation	
eCl@ss 5.1.4	21040301
ETIM 5.0	EC000164
ETIM 6.0	EC000164
proficl@ss 6.0	AAA936c004

technical change and errors excepted