
## **KEMET Part Number: CK06BX223K**

(C062K223K1X5CA)



LDD Mil X7R C11015, Ceramic, 0.022 uF, 10%, 100 VDC, BX, N/A, Lead Spacing = 5.08mm



Dimensions		
L	7.37mm +/-0.25mm	
Н	7.37mm +/-0.25mm	
Т	2.29mm +/-0.25mm	
S	5.08mm +/-0.38mm	
LL	31.75mm MIN	
F	0.635mm +/-0.051mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	100	

General Information		
Series:	LDD Mil X7R C11015	
Style:	Radial	
RoHS:	No	
Prop 65:	warning: Cancer and reproductive harm - www.p65warnings.ca.gov.	
SCIP Number:	8c864fd1-202b-4ce7-85fd-56c9e1	.9121ad
Termination:	Lead (SnPb)	
Failure Rate:	N/A	
Testing and Reliability:	MIL-PRF-11015	
Qualifications:	MIL-PRF-11015	
AEC-Q200:	No	
Notes:	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.	

Specifications		
Capacitance:	0.022 uF	
Capacitance Tolerance:	10%	
Voltage DC:	100 VDC	
Dielectric Withstanding Voltage:	250 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	ВХ	
Dissipation Factor:	2.5%	
Insulation Resistance:	45.5 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

