
## KEMET Part Number: R474I23305001K Not for New Design

(474I23305001K)



R47 X2 440 VAC, Film, Metallized Polypropylene, Automotive Safety, 0.033 uF, 10%, 440 VAC (X2), 1000 VDC, 110°C, Lead Spacing = 15mm



Dimensions		
L	18mm +0.3/-0.5mm	
Н	12mm +0.1/-0.5mm	
Т	6mm +0.2/-0.5mm	
S	15mm +/-0.4mm	
LL	25mm +2/-1mm	
F	0.6mm +/-0.05mm	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	900	

General Information	
Series:	R47 X2 440 VAC
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	Automotive Grade, EMI Safety
RoHS:	Yes
Lead:	Wire Leads
Safety Class:	X2
Qualifications:	AEC-Q200, ENEC, UL, cUL
AEC-Q200:	Yes
THB Performance:	No
Component Weight:	2 g

Specifications		
Capacitance:	0.033 uF	
Capacitance Tolerance:	10%	
Voltage AC:	440 VAC (X2)	
Voltage DC:	1000 VDC	
Temperature Range:	-40/+110°C	
Rated Temperature:	110°C	
Dissipation Factor:	0.3% 1kHz	
Insulation Resistance:	100 GOhms	
Max dV/dt:	600 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

