MTi-300

- Xsens' high-performance product line
- 0.2 deg in roll/pitch, 1 deg in heading accuracy
- Complete SDK and development kits available

The MTi-300 is a high-performing Attitude Heading and Reference System (AHRS). It features vibration-rejecting gyroscopes and offers high-quality inertial data, even in challenging environments. The MTi-300 supports optimized temperature calibration, high-frequency outputs, and has configurable output settings for synchronization with any third-party device.

The MTi-300 is part of the MTi 100-series supported by the MT Software Suite, which includes MT Manager (GUI for Windows/Linux), SDK, example codes and drivers for many platforms.



- White label and OEM integration options available
- 3D models available on request
- Available online via Digi-Key, Mouser, Farnell and local distributors

Roll, Pitch	0.2 deg RMS
Yaw/Heading	1 deg RMS
Strapdown Integration (SDI)	Yes
Gyroscope	
Standard full range	450 deg/s
In-run bias stability	10 deg/h
Bandwidth (-3dB)	415 Hz

otaniaana ran rango	.00 409/0
In-run bias stability	10 deg/h
Bandwidth (-3dB)	415 Hz
Noise Density	0.01 °/s/√Hz
g-sensitivity (calibr.)	0.003 °/s/g

Sensor fusion performance

Accelerometer

Standard full range	20 g
In-run bias stability	15 μg
Bandwidth (-3dB)	375 Hz
Noise Density	60 µg/√Hz

Magnetometer	
Standard full range	+/- 8 G
Total RMS noise	0.5 mG
Non-linearity	0.2%
Resolution	0.25 mG

GNSS Receiver	
Brand	n/a
Model	n/a
RTCM input port	—— n/a

Barometer	
Standard full range	300-1100 hPa
Total RMS noise	3.6 Pa
Resolution	~0.08m

Mechanical

IP-rating	IP67
Operating Temperature ————	-40 to 85 °C
Casing material	Aluminum
Mounting orientation	No restriction, full 360° in all axes
Dimensions ————————————————————————————————————	57x41.90x23.60 mm
Connector	Fischer SV
Weight	55 g

Electrical

Input voltage ————	3V3, 4.5V-34V
Power consumption (typ)	520 mW

Interfaces / IO

Interfaces	USB, RS232, RS422, UART
Sync Options	SyncIn, SyncOut, ClockSync
Protocols	Xbus, ASCII (NMEA)
Clock drift	10 ppm (or external)
Output Frequency	up to 2kHz
Built-in-self test	Yes

Software Suite

GUI (Windows/Linux)	MT Manager Firmware updater,
	Magnetic Field Mapper
SDK (Example code)	C++, C#, python, Matlab, Nucleo,
	public source code
Drivers	LabVIEW, ROS, GO
Support	BASE by XSENS: online manuals,
	community and knowledge base



