



## Key Features

- 6.3 x 32mm fuses
- Screwdriver slot knob
- PC2 protection category
- 4.8, 6.3 and solder terminals
- Low profile bezel
- Snap in or threaded bushing mounting options

## Approvals and specifications

Ⓢ 10A 250V (max fuse rating\*) T-55 to T+70 (ambient)  
Maximum dissipation wattage: 4W

 16A UL 250V UL file E92075 CSA file LR44770


These products comply with safety category PC2.

\*Users should be aware of the de-rating factors published by specialist manufacturers of fuses.




Fuseholders with Inline termination have combination (4.8/6.3) terminals. It has not been possible to show both views here. Units with right angle terminals have user specified end terminals and combination mid-body terminals.

<b>T</b>	/	<b>0347</b>	/	<b>RA</b>	/	<b>----</b>
Terminal		Body & Cap		Panel Hole		Options

## Terminal

**C**

6.3 x 0.8

**D**6.3 x 0.8  
Right Angle**T**4.8 x 0.8  
Solder**U**4.8 x 0.8  
Right Angle

## Body


**0345** (C terminal shown)  
Screwdriver release

**0345** (D terminal shown)  
Screwdriver release


**0347** (T terminal shown)  
Screwdriver release

**0347** (U terminal shown)  
Screwdriver release


## Options

**RA**


Panel thickness  
0.8 - 2.0mm for snap fit  
0.8 - 7.0mm for screw to  
panel fixing

**RD**


Panel thickness  
0.8 - 2.0mm for snap fit  
0.8 - 7.0mm for screw to  
panel fixing

## Dimensions


0345 (C terminal shown)




0345 (D terminal shown)



0347 (C terminal shown)



0347 (D terminal shown)



Optional metal fixing nut available for 0347