



























Produktübersicht
Product Summary
Aperçu général des produits



Symbolerklärungen / Symbol Definition / Signification des symboles

Piktogramme / Guiding icons / Pictogrammes

	Federkraftklemme Spring clamp terminal block Borniers à ressort		Drahtschutz Wire protector Protège-fil
	Schneidklemme IDC terminal block Borniers à déplacement d'isolant		anreihbar modular Modulaire
	Schraubklemme Screw type terminal block Borniers à vis		Stiftleiste vertikal Pin header for vertical mounting Embase verticale
	Stiftleiste Pin header Embases à picots		Stiftleiste vertikal mit Führung Shrouded pin header for vertical mounting Embase verticale avec cloison arrière
	Buchsenleiste Female connector Embases femelles		Stiftleiste vertikal offene Wanne Pin header with open ends for vertical mounting Embase verticale sans cloisons latérales
	Ethernet M12		Stiftleiste vertikal geschlossene Wanne Pin header with closed ends for vertical mounting Embase verticale avec cloisons latérales
	lötbar solderable Soudable		Stiftleiste horizontal Pin header for horizontal mounting Embase horizontale
	steckbar pluggable Enfichable		Stiftleiste horizontal mit Führung Shrouded pin header for horizontal mounting Embase horizontale avec cloison arrière
	Rastermaß Centerline Pas		Stiftleiste horizontal offene Wanne Pin header with open ends for horizontal mounting Embase horizontale sans cloisons latérales
	Anschlussrichtung 90° Wire entry 90° Sens de connexion 90°		Stiftleiste horizontal geschlossene Wanne Pin header with closed ends for horizontal mounting Embase horizontale avec cloisons latérales
	Anschlussrichtung diagonal Diagonal wire entry Sens de connexion diagonale		entwickelt für THR designed for THR Convient pour THR
	Anschlussrichtung 0° Wire entry 0° Sens de connexion 0°		entwickelt für SMT designed for SMT Convient pour CMS
	Liftsystem Lift system Système à cage		Tape & Reel möglich Tape & Reel possible Emballage en ruban (Tape & Reel) possible

Federkraftklemmen,
löt- und steckbar
Spring clamp terminal blocks,
solderable and pluggable
Borniers à ressort,
soudables et enfichables

Federkraftklemme
Spring clamp
terminal block
Borniers à ressort

lötbar
solderable
soudable

entwickelt für THR
designed for THR
convient pour THR

Rastermaß
Centerline
Pas

Anschlussrichtung 90°
Wire entry 90°
Sens de connexion 90°

Anschlussrichtung
diagonal
Diagonal wire entry
Sens de connexion
diagonale

Anschlussrichtung 0°
Wire entry 0°
Sens de connexion 0°

Tape & Reel möglich
Tape & Reel possible
Emballage en ruban
(Tape & Reel) possible

Zulassung in
Vorbereitung
Approval pending
Homologation en
cours

Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

23



ST061xxHDNN *(AST061)

150 V / 8 A / 28 - 20
130 V / 6 A / 0.5 mm²

23



ST021xxHDNN *(AST021)

150 V / 8 A / 28 - 20
130 V / 6 A / 0.5 mm²


24



ST041xxDDNN *(AST041)

150 V / 8 A / 28 - 18
130 V / 6 A / 0.5 mm²


25



ST072xxHGNN *(AST072)

150 V / 6 A / 26 - 20
130 V / 6 A / 0.5 mm²


25



ST072xxVGNN *(AST082)

150 V / 6 A / 26 - 20
130 V / 6 A / 0.5 mm²


26



SR213xxHBNC *(AST223)

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²


26



SR213xxHBPC

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²


27



SR213xxDBNC *(AST233)

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²

27



SR213xxDBPC

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²


28



SR213xxVBNC *(AST213)

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²

28



SR213xxVBPC

150 V / 10 A / 28 - 16
130 V / 17.5 A / 1.5 mm²


29



ST024xxHDNC *(AST024)

150 V / 7 A / 28 - 20
250 V / 6 A / 0.5 mm²


30



SR215xxHBNC *(AST225)

300 V / 10 A / 28 - 16
250 V / 17.5 A / 1.5 mm²

30



SR215xxHBPC

300 V / 10 A / 28 - 16
250 V / 17.5 A / 1.5 mm²

31



ST065xxHDNN *(AST065)

300 V / 13 A / 28 - 14
250 V / 13.5 A / 1 mm²

31



ST025xxHDNC *(AST025)

300 V / 13 A / 28 - 14
250 V / 13.5 A / 1 mm²


32



ST055xxHBNC *(AST055)

300 V / 12 A / 28 - 12
160 V / 19 A / 2.5 mm²


32



SR255xxHBNC

300 V / 18 A / 24 - 12
250 V / 9 A / 0.75 mm²


30



ST255XXHDNL

300 V / 12 A / 24 - 12
250 V / 9 A / 0.75 mm²

30



ST255XXHDNR

300 V / 12 A / 24 - 12
250 V / 9 A / 0.75 mm²

32



ST095xxHDNN *(AST095)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

33



SR215xxDBNC *(AST235)

300 V / 10 A / 28 - 16
250 V / 17.5 A / 1.5 mm²

33



ST045xxDDNC *(AST045)

300 V / 13 A / 28 - 16
250 V / 13.5 A / 1 mm²

34



ST135xxDDNC *(AST135)

300 V / 13 A / 28 - 12
160 V / 19 A / 2.5 mm²

34



ST175xxLDNN *(AST175)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

35



ST185xxLDNN *(AST185)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²


35



SR215xxVBNC *(AST215)

300 V / 10 A / 28 - 16
250 V / 17.5 A / 1.5 mm²


36



SR215xxVBPC

300 V / 10 A / 28 - 16
250 V / 17.5 A / 1.5 mm²

36



ST105xxVDNN *(AST105)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

37



ST125xxVDNN *(AST125)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

37



ST145xxVDNN *(AST145)

300 V / 17 A / 28 - 14
450 V / 17.5 A / 1.5 mm²

38



ST176xxLDNN *(AST176)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

38



ST186xxLDNN *(AST186)

300 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

39



ST067xxHDNN *(AST067)

600 V / 13 A / 28 - 14
750 V / 13.5 A / 1 mm²

39



ST027xxHDNC *(AST027)

300 V / 13 A / 28 - 14
750 V / 13.5 A / 1 mm²


40



ST057xxHBNC *(AST057)

300 V / 17 A / 28 - 12
320 V / 19 A / 2.5 mm²

41



SR207xxDBVN

300 V / 16 A / 20 - 14
250 V / 24 A / 2.5 mm²

41



ST047xxDDNC *(AST047)

600 V / 13 A / 28 - 14
750 V / 13.5 A / 1 mm²

41



ST137xxDDNC *(AST137)

300 V / 13 A / 28 - 12
320 V / 19 A / 2.5 mm²

42



ST177xxLDNN *(AST177)

600 V / 15 A / 28 - 12
250 V / 13.5 A / 1 mm²

Federkraftklemmen,
löt- und steckbar
Spring clamp terminal blocks,
solderable and pluggable
Borniers à ressort,
soudables et enfichables

Federkraftklemme
Spring clamp
terminal block
Borniers à ressort

Schraubklemme
Screw type terminal block
Borniers à vis

lötbar
solderable
soudable

steckbar
pluggable
enfichable

entwickelt für THR
designed for THR
convient pour THR

entwickelt für SMT
designed for SMT
convient pour CMS

Rastermaß
Centerline
Pas

Anschlussrichtung 90°
Wire entry 90°
Sens de connexion 90°

Anschlussrichtung
diagonal
Diagonal wire entry
Sens de connexion
diagonale

Anschlussrichtung 0°
Wire entry 0°
Sens de connexion 0°

Drahtschutz
Wire protector
Protège-fil

Liftsystem
Lift system
Système à cage

Tape & Reel möglich
Tape & Reel possible
Emballage en ruban
(Tape & Reel) possible

Zulassung in
Vorbereitung
Approval pending
Homologation en
cours

Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

42



ST187xxLDNN *(AST187)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

43



ST098xxHDNN *(AST098)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

43



ST178xxLDNN *(AST178)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

44




ST188xxLDNN *(AST188)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

44



ST108xxVDNN *(AST108)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

45




ST128xxVDNN *(AST128)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 15 A / 28 - 12
IEC: 250 V / 13.5 A / 1 mm²

46




ST059xxHBNC *(AST059)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 600 V / 12 A / 28 - 12
IEC: 500 V / 19 A / 2.5 mm²

46



ST139xxDDNC *(AST139)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 13 A / 28 - 12
IEC: 500 V / 19 A / 2.5 mm²

47



SP051xxVGNN *(ASP051)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 5 A / 28 - 20
IEC: 80 V / 6 A / 0.08-0.5 mm²

48




SP043xxVBNN *(ASP043)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 10 A / 28 - 16
IEC: 130 V / 10 A / 0.08-1.5 mm²

48




SW063xxVBNN

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 8 A / 28 - 16
IEC: 130 V / 8 A / 0.08-1.5 mm²

49




SP063xxVGNN *(ASP063)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 8 A / 28 - 16
IEC: 130 V / 8 A / 0.08-1.5 mm²

49




SP063xxVGNF *(ASP063)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 8 A / 28 - 16
IEC: 130 V / 8 A / 0.08-1.5 mm²

50




SP044xxVBNN *(ASP044)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 10 A
IEC: 130 V / 10 A / 0.08-1.5 mm²

50




SP064xxVGNN *(ASP064)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 8 A / 28 - 16
IEC: 130 V / 9 A / 0.08-1.5 mm²

51




SP064xxVGNF *(ASP064)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 8 A / 28 - 16
IEC: 130 V / 9 A / 0.08-1.5 mm²

52




SP025xxHDNC *(ASP025)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 8 A / 28 - 16
IEC: 250 V / 10 A / 0.08-1.5 mm²

52




SP145xxHBNC *(ASP145)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 6 A / 28 - 16
IEC: 250 V / 13.5 A / 0.08-1.5 mm²

53




SP155xxHBNC *(ASP155)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 6 A / 28 - 16
IEC: 250 V / 13.5 A / 0.08-1.5 mm²

53




SP045xxVBNC *(ASP045)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 10 A / 28 - 16
IEC: 250 V / 10 A / 0.08-1.5 mm²

54




SP065xxVBNC

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

54




SP065xxVBPC

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

55




SP065xxVBPF

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

55



SP065xxVBPF

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

56



SP995xxVBNC

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 14 A / 24 - 14
IEC: 250 V / 12 A / 0.2-2.5 mm²

57



SP046xxVBNC *(ASP046)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 10 A / 28 - 16
IEC: 250 V / 10 A / 0.08-1 mm²

57




SP066xxVBNC

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

58




SP066xxVBPC

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

58




SP066xxVBPF

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

59



SP066xxVBPF

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 12 A / 28 - 12
IEC: 250 V / 12 A / 0.08-2.5 mm²

60



SP049xxVBNC *(ASP049)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 8 A / 28 - 16
IEC: 630 V / 10 A / 0.08-1 mm²

60




SP129xxVBNF *(ASP129)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 300 V / 10 A / 28 - 12
IEC: 630 V / 12 A / 0.08-2.5 mm²

61




SP04AxxVBNC *(ASP04A)

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

IEC: 630 V / 10 A / 0.08-1 mm²

61




SC303xxHBNN

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 4 A / 28 - 16
IEC: 130 V / 4 A / 0.08-1.5 mm²

61




SL303xxHBNN

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 150 V / 4 A / 28 - 16
IEC: 130 V / 4 A / 0.08-1.5 mm²

62




SC305xxHBNN

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 250 V / 4 A / 28 - 16
IEC: 250 V / 4 A / 0.08-1.5 mm²

62



SL305xxHBNN

Icons: Spring clamp, solderable, pluggable, diagonal wire entry

UL: 350 V / 4 A / 28 - 16
IEC: 250 V / 4 A / 0.08-1.5 mm²

63



SM99S

Icons: Spring clamp, solderable, pluggable, diagonal wire entry, THR, SMT

UL: 9 A / 24 - 16
IEC: 9 A / 0.2-1.5 mm²

63




SR99S

Icons: Spring clamp, solderable, pluggable, diagonal wire entry, THR, SMT

UL: 9 A / 24 - 16
IEC: 9 A / 0.2-1.5 mm²

64




SM01W

Icons: Spring clamp, solderable, pluggable, diagonal wire entry, SMT


IEC: 13 A / 0.1-0.75 mm²

Federkraftklemmen,
löt- und steckbar
Spring clamp terminal blocks,
solderable and pluggable
Borniers à ressort,
soudables et enfichables

64




SM01Y




13 A / 0.75-1.5 mm²

SM02V




SM02V




4 A / 0.25-0.5 mm²

Schraubklemmen,
löt- und steckbar
Screw type terminal blocks,
solderable and pluggable
Borniers à vis,
soudables et enfichables

69




RT063xxHBNC *(Type 060)




125 V / 15 A / 20 - 14
125 V / 13.5 A / 1 mm²

69




RT063xxHBWC *(Type 059)




150 V / 10 A / 28 - 16
125 V / 13.5 A / 1 mm²

70




RT063xxOBWC *(Type 459)




300 V / 7 A / 28 - 16
125 V / 13.5 A / 1.5 mm²

70




RT063xxPBWC *(Type 461)




300 V / 15 A / 28 - 16
125 V / 13.5 A / 1 mm²

71



RT033xxHBLU *(Type 359)



150 V / 10 A / 28 - 16
130 V / 12 A / 1.0 mm²

Schraubklemme
Screw type terminal block
Borniers à vis

lötbar
solderable
soudable

5.00
Rastermaß
Centerline
Pas

Anschlussrichtung 90°
Wire entry 90°
Sens de connexion 90°

Anschlussrichtung
diagonal
Diagonal wire entry
Sens de connexion
diagonale

Anschlussrichtung 0°
Wire entry 0°
Sens de connexion 0°

anreihbar
modular
modulaire


Drahtschutz
Wire protector
Protège-fil

Liftsystem
Lift system
Système à cage


Zulassung in
Vorbereitung
Approval pending
Homologation en
cours

Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

71




RT083xxDBWC *(Type 105)




300 V / 10 A / 28 - 16
130 V / 13.5 A / 1.0 mm²

72




RT043xxLBLE *(Type 305)




300 V / 10 A / 28 - 16
130 V / 13.5 A / 1.0 mm²

72




RT063xxVBWC *(Type 061)




150 V / 10 A / 28 - 16
125 V / 13.5 A / 1.0 mm²

73



RT033xxVBLU *(Type 361)



150 V / 10 A / 28 - 16
130 V / 12 A / 1.0 mm²

74




RT034xxHBLC *(Type 086)




150 V / 10 A / 28 - 18
130 V / 13.5 A / 1.0 mm²

75




RT015xxHDWC *(Type 001)




300 V / 15 A / 22 - 14
130 V / 17.5 A / 1.5 mm²

75




RT015xxHDWU *(Type 055)




300 V / 15 A / 22 - 14
130 V / 13 A / 1.5 mm²

76




RT135xxHBWC *(Type 271)




300 V / 15 A / 26 - 14
250 V / 24 A / 2.5 mm²

76




RT045xxHBWC *(Type 003)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

77




RT045xxMBWC *(Type 069)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

77




RT055xxHBLC *(Type 011)




300 V / 15 A / 28 - 12
250 V / 17.5 A / 1.5 mm²

78




RT025xxHBLC *(Type 071)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

78




RT025xxHBLU *(Type 072)




300 V / 20 A / 22 - 12
250 V / 16 A / 2.5 mm²

79




RT145xxMBLC *(Type 204)




300 V / 15 A / 28 - 12
250 V / 16 A / 2.5 mm²

79




RT145xxMBLC *(Type 269)




300 V / 15 A / 28 - 12
250 V / 16 A / 2.5 mm²

80




RT165xxHBNC *(Type 170)




300 V / 20 A / 20 - 10
250 V / 24 A / 2x2.5 mm²

80




RT035xxHBLU *(Type 094)




300 V / 10 A / 26 - 16
250 V / 17.5 A / 1.5 mm²

81




RT075xxHBLU *(Type 092)




300 V / 10 A / 26 - 16
250 V / 17.5 A / 1.5 mm²

81




RT205xxHBLU *(Type 096)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

82




RT025xxOGLU *(Type 065)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

82




RT025xxHDLL *(Type 385)




300 V / 20 A / 20 - 12
250 V / 24 A / 2.5 mm²

83




RT025xxHDLR *(Type 386)




300 V / 20 A / 20 - 12
250 V / 24 A / 2.5 mm²

83




RT085xxDBWC *(Type 005)




300 V / 20 A / 22 - 12
250 V / 24 A / 2.5 mm²

84




RT045xxUBLU *(Type 205)




300 V / 15 A / 28 - 12
250 V / 24 A / 2.5 mm²

84




RT015xxVDWC *(Type 063)




300 V / 15 A / 22 - 14
130 V / 13 A / 1.5 mm²

85




RT095xxVBWC *(Type 147)




300 V / 15 A / 22 - 14
250 V / 17.5 A / 1.5 mm²

86




RT016xxHBWC *(Type 101)




300 V / 15 A / 28 - 14
130 V / 13 A / 1.5 mm²

86




RT056xxHBLU *(Type 015)




300 V / 15 A / 22 - 14
250 V / 17.5 A / 1.5 mm²

87




RT036xxHBLU *(Type 095)




300 V / 10 A / 26 - 16
250 V / 17.5 A / 1.5 mm²

87



RT046xxHBWU *(Type 083)



300 V / 20 A / 22 - 14
250 V / 24 A / 2.5 mm²

Schraubklemmen,
löt- und steckbar
Screw type terminal blocks,
solderable and pluggable
Borniers à vis,
soudables et enfichables

Schraubklemme
Screw type terminal block
Borniers à vis

lötbar
solderable
soudable

steckbar
pluggable
enfichable

Rastermaß
Centerline
Pas

Anschlussrichtung 90°
Wire entry 90°
Sens de connexion 90°

Anschlussrichtung diagonal
Diagonal wire entry
Sens de connexion diagonale

Anschlussrichtung 0°
Wire entry 0°
Sens de connexion 0°

Drahtschutz
Wire protector
Protège-fil

Liftsystem
Lift system
Système à cage

anreihbar
modular
modulaire

Zulassung in Vorbereitung
Approval pending
Homologation en cours

Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

88

RT076xxHBLU *(Type 093)

U_N 300 V / 10 A / 26 - 16
I_N 250 V / 17.5 A / 1.5 mm²

88

RT206xxHBLU *(Type 097)

U_N 300 V / 20 A / 22 - 12
I_N 250 V / 24 A / 2.5 mm²

89

RT026xxHBLU *(Type 073)

U_N 300 V / 20 A / 22 - 12
I_N 250 V / 16 A / 2.5 mm²

89

RT016xxVBWC *(Type 163)

U_N 300 V / 15 A / 28 - 14
I_N 130 V / 13 A / 1.5 mm²

90

RT11LxxHGLU *(Type 701)

U_N 300 V / 30 A / 26 - 10
I_N 450 V / 32 A / 4 mm²

91

RT137xxHBWC *(Type 171)

U_N 300 V / 15 A / 26 - 14
I_N 450 V / 24 A / 2.5 mm²

91

RT027xxHBLC *(Type 175)

U_N 300 V / 20 A / 22 - 12
I_N 750 V / 24 A / 2.5 mm²

92

RT10NxxHGLU *(Type 703)

U_N 300 V / 30 A / 26 - 10
I_N 800 V / 32 A / 4 mm²

93

RT019xxHDWC *(Type 001)

U_N 600 V / 15 A / 22 - 14
I_N 750 V / 17.5 A / 1.5 mm²

93

RT019xxHDWC *(Type 067)

U_N 300 V / 15 A / 22 - 14
I_N 750 V / 13 A / 1.5 mm²

94

RT139xxHBWC *(Type 271)

U_N 300 V / 15 A / 26 - 14
I_N 750 V / 24 A / 2.5 mm²

94

RT049xxHBWC *(Type 003)

U_N 600 V / 20 A / 22 - 12
I_N 630 V / 24 A / 2.5 mm²

95

RT049xxMBWC *(Type 069)

U_N 600 V / 20 A / 22 - 12
I_N 630 V / 24 A / 2.5 mm²

95

RT059xxHBLC *(Type 011)

U_N 600 V / 15 A / 22 - 12
I_N 500 V / 17.5 A / 1.5 mm²

96

RT029xxHBLC *(Type 071)

U_N 600 V / 20 A / 22 - 12
I_N 750 V / 24 A / 2.5 mm²

96

RT149xxMBLC *(Type 269)

U_N 600 V / 15 A / 28 - 12
I_N 630 V / 16 A / 2.5 mm²

97

RT049xxUBLC *(Type 205)

U_N 600 V / 15 A / 28 - 12
I_N 250 V / 24 A / 2.5 mm²

97

RT019xxVDWC *(Type 063)

U_N 600 V / 15 A / 22 - 14
I_N 750 V / 13 A / 1.5 mm²

98

RT099xxVBWC *(Type 147)

U_N 600 V / 15 A / 22 - 14
I_N 800 V / 17.5 A / 1.5 mm²

99

RT01AxxVBWC *(Type 163)

U_N 600 V / 15 A / 28 - 14
I_N 750 V / 13 A / 1.5 mm²

100

RP023xxHBWC *(Type 166)

U_N 125 V / 8 A / 28 - 16
I_N 200 V / 6 A / 0.08-1 mm²

100

RP023xxHBNF *(Type 165)

U_N 125 V / 10 A / 28 - 16
I_N 200 V / 6 A / 0.08-1 mm²

101

RP043xxHBLC *(Type 614)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.34-1 mm²

101

RP043xxHBLD *(Type 613)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.34-1 mm²

102

RP043xxHBLF *(Type 634)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.34-1 mm²

102

RP043xxHBLS *(Type 633)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.34-1 mm²

103

RW043xxHBLC *(Type 514)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.08-1 mm²

103

RW043xxHBLD *(Type 513)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.08-1 mm²

104

RW043xxHBLF *(Type 534)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.08-1 mm²

104

RW043xxHBLS *(Type 533)

U_N 300 V / 10 A / 28 - 16
I_N 130 V / 10 A / 0.08-1 mm²

105

RP013xxVBWN *(Type 169)

U_N 250 V / 10 A / 28 - 16
I_N 125 V / 5 A / 0.08-1 mm²

105

RP033xxVBLC *(Type 339)

U_N 300 V / 8 A / 28 - 16
I_N 125 V / 9 A / 0.08-1.5 mm²

106

RP034xxHBLN *(Type 114)

U_N 300 V / 11 A / 28 - 16
I_N 160 V / 9 A / 0.08-1.5 mm²

106

RP043xxHBLO *(Type 113)

U_N 300 V / 11 A / 28 - 16
I_N 160 V / 9 A / 0.08-1.5 mm²

107

RP034xxVBLN *(Type 369)

U_N 300 V / 8 A / 28 - 16
I_N 160 V / 9 A / 0.08-1.5 mm²

107

RP034xxVBFL *(Type 379)

U_N 300 V / 8 A / 28 - 16
I_N 160 V / 9 A / 0.08-1.5 mm²

108

RP025xxHBWC *(Type 007)

U_N 300 V / 15 A / 22 - 12
I_N 250 V / 10 A / 0.33-2.5 mm²

108

RP025xxIBWU *(Type 077)

U_N 300 V / 15 A / 22 - 14
I_N 250 V / 10 A / 0.33-2.5 mm²

109

RP025xxHBWC *(Type 107)


U_N 300 V / 10 A / 28 - 12
I_N 250 V / 10 A / 0.33-2.5 mm²


109

RP025xxMBWC *(Type 108)

U_N 300 V / 10 A / 28 - 12
I_N 250 V / 10 A / 0.33-2.5 mm²


Schraubklemmen,
löt- und steckbar
Screw type terminal blocks,
solderable and pluggable
Borniers à vis,
soudables et enfichables

 Schraubklemme
Screw type terminal block
Borniers à vis


 Schneidklemme
Spring clamp
terminal block
Borniers à déplacement
d'isolant


 lötbar
solderable
soudable


 steckbar
pluggable
enfichable


 entwickelt für THR
designed for THR
convient pour THR


 Rastermaß
Centerline
Pas

 Anschlussrichtung 90°
Wire entry 90°
Sens de connexion 90°


 Anschlussrichtung
diagonal
Diagonal wire entry
Sens de connexion
diagonale


 Anschlussrichtung 0°
Wire entry 0°
Sens de connexion 0°

 Drahtschutz
Wire protector
Protège-fil


 Liftsystem
Lift system
Système à cage

 Tape & Reel möglich
Tape & Reel possible
Emballage en ruban
(Tape & Reel) possible


 Zulassung in
Vorbereitung
Approval pending
Homologation en
cours

 Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

110




RP025xxHBLC *(Type 207)




300 V / 15 A / 28 - 12
250 V / 10 A / 0.08-2.5 mm²

110




RP025xxIBLC *(Type 137)




300 V / 15 A / 26 - 12
250 V / 10 A / 0.12-2.5 mm²

111




RP095xxRBWC *(Type 157)




300 V / 5 A / 28 - 20
250 V / 13.5 A / 0.08-2.5 mm²

111




RP095xxBBWC *(Type 157)




300 V / 5 A / 28 - 20
250 V / 13.5 A / 0.08-2.5 mm²

112




RP059xxHBWC *(Type 157)




300 V / 5 A / 28 - 20
250 V / 13.5 A / 0.08-2.5 mm²

112



RP015xxWBWC *(Type 009)



300 V / 15 A / 22 - 12
150 V / 13.5 A / 0.08-2.5 mm²

113




RP015xxWBLC *(Type 049)




300 V / 15 A / 22 - 12
320 V / 13.5 A / 0.08-2.5 mm²

113




RP015xxVBLC *(Type 349)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

114




RP015xxSBLC *(Type 350)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

114




RP015xxVBLC *(Type 351)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

115



RP085xxVBLC *(Type 348)



300 V / 17 A / 24 - 12
250 V / 12 A / 0.08-2.5 mm²

115



RP035xxIBLN *(Type 013)



300 V / 15 A / 22 - 12
320 V / 13.5 A / 0.08-2.5 mm²

116




RP035xxHBLC *(Type 313)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

116




RP035xxHBLD *(Type 314)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

117




RP995xxVDNN




300 V / 6 A / 24 - 12

118




RP026xxIBWU *(Type 079)




300 V / 15 A / 22 - 14
125 V / 10 A / 0.33-2.5 mm²

118




RP016xxVBLC *(Type 249)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

119




RP016xxSBLC *(Type 250)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

119




RP016xxVBLC *(Type 251)




300 V / 16 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

120




RP036xxHBLC *(Type 213)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

120




RP036xxHBLD *(Type 214)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

121




RP036xxHBLF *(Type 217)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

121




RP036xxHBLS *(Type 218)




300 V / 12 A / 28 - 12
320 V / 13.5 A / 0.08-2.5 mm²

122




RP018xxVBLC *(Type 262)




300 V / 15 A / 28 - 14
500 V / 13.5 A / 0.08-2.5 mm²

123




RP029xxIBWC *(Type 007)



600 V / 15 A / 22 - 12
630 V / 10 A / 0.33-2.5 mm²

123



RP019xxWBLC *(Type 049)



600 V / 15 A / 22 - 12
630 V / 13.5 A / 0.08-2.5 mm²

124




RP039xxHBLC *(Type 313)




600 V / 12 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

124




RP019xxVBLC *(Type 349)




600 V / 16 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

125




RP019xxVBLC *(Type 351)




600 V / 16 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

126




RP01AxxVBLC *(Type 249)




600 V / 16 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

126



RP01AxxVBLC *(Type 251)



600 V / 16 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

127



RP03AxxHBLC *(Type 213)



600 V / 12 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

127



RP03AxxHBLD *(Type 214)



600 V / 12 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

128



RP03AxxHBLF *(Type 217)



600 V / 12 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

128




RP03AxxHBLS *(Type 218)




600 V / 12 A / 28 - 12
630 V / 13.5 A / 0.08-2.5 mm²

129




360272




15 A / 26 - 14

129




360273




15 A / 26 - 14

130




360410




15 A / 30 - 18

130




360322




15 A / 30 - 16
15 A / 30 - 16

131




360381



16 A / 0.5-2.5 mm²

Schraubklemmen,
löt- und steckbar
Screw type terminal blocks,
solderable and pluggable
Borniers à vis,
soudables et enfichables


131



360291

50 V / 15 A / 22 - 14


132



360271

50 V / 15 A / 24 - 14

132




360425

THR

Schneidklemmen, lötlbar
IDC type terminal blocks,
solderable
Borniers à déplacement d'isolant,
soudables

137




IT023xxHDNU *(AIT023)

150 V / 2.5 A / 24 - 22
130 V / 5 A / 0.34 mm²

Stiftleisten für
Federkraftklemmen und
Schraubklemmen
Pin headers for spring type
terminal blocks and screw
type terminal blocks
Embases pour borniers
à ressort et borniers à vis


145



PT091xxHGBN *(Type 374)

150 V / 5 A
80 V / 6 A


145



PT091xxVGBN *(Type 373)

150 V / 5 A
80 V / 6 A


146



PR013xxVBHC *(Type 024)

125 V / 10 A


146



PR043xxHBBN *(Type 188)

300 V / 10 A
130 V / 10 A

147



PR043xxHBBF *(Type 388)

300 V / 10 A
130 V / 10 A

Stiftleiste
Pin header
Embases à picots

lötbar
solderable
soudable

entwickelt für THR
designed for THR
convient pour THR

entwickelt für SMT
designed for SMT
convient pour CMS

5.00
Rastermaß
Centerline
Pas

Stiftleiste vertikal
Pin header for vertical
mounting
Embase verticale

Stiftleiste vertikal
offene Wanne
Pin header with open
ends for vertical
mounting
Embase verticale sans
cloisons latérales


Stiftleiste vertikal
geschlossene Wanne
Pin header with closed
ends for vertical
mounting
Embase verticale avec
cloisons latérales

Stiftleiste horizontal
geschlossene Wanne
Pin header with closed
ends for horizontal
mounting
Embase horizontale
avec cloisons latérales

Tape & Reel möglich
Tape & Reel possible
Emballage en ruban
(Tape & Reel) possible

Zulassung in
Vorbereitung
Approval pending
Homologation en
cours


147



PW063xxHBEC *(Type 527)

300 V / 10 A
130 V / 10 A


148



PW063xxHBBN *(Type 523)

300 V / 10 A
130 V / 10 A


148



PW063xxHBBF *(Type 525)

300 V / 10 A
130 V / 10 A


149



PT093xxHBBN *(Type 342)

300 V / 8 A
125 V / 9 A


149



PT093xxHBBF *(Type 394)

300 V / 8 A
125 V / 9 A


150



PT113xxHBBN *(Type 182)

300 V / 10 A
125 V / 6 A


150



PR033xxVBHC *(Type 224)

300 V / 15 A
SEV Reg 130002 200 V / 6 A


151



PR043xxVBBN *(Type 189)

300 V / 10 A
130 V / 10 A


151



PR043xxVBBF *(Type 389)

300 V / 10 A
130 V / 10 A


152



PW063xxVBBF *(Type 528)

300 V / 10 A
130 V / 10 A


152



PW063xxVBBN *(Type 524)

300 V / 10 A
130 V / 10 A


153



PW063xxVBBF *(Type 526)

300 V / 10 A
130 V / 10 A


153



PM013xxVBHC *(Type 424)

300 V / 15 A


154



PT093xxVBBN *(Type 343)

300 V / 8 A
125 V / 9 A


154



PT113xxVBBN *(Type 183)

300 V / 10 A
125 V / 6 A


155



PR044xxHBBN *(Type 190)

300 V / 8 A
130 V / 10 A


155



PR044xxHBBF *(Type 390)

300 V / 8 A
130 V / 10 A


156



PT094xxHBBN *(Type 382)

300 V / 8 A
160 V / 9 A


156



PT094xxHBBF *(Type 392)

300 V / 8 A
160 V / 9 A


157



PR044xxVBBN *(Type 191)

300 V / 8 A
130 V / 10 A


157



PR044xxVBBF *(Type 391)

300 V / 8 A
130 V / 10 A


158



PT094xxVBBN *(Type 383)

300 V / 8 A
160 V / 9 A

158



PT094xxVBBF *(Type 393)

300 V / 8 A
160 V / 9 A


159



PR065xxHBEC *(Type 476)

300 V / 15 A
320 V / 13.5 A











159



PR065xxHBBN *(Type 176)

300 V / 15 A
320 V / 13.5 A

Stiftleisten für
Federkraftklemmen und
Schraubklemmen
Pin headers for spring type
terminal blocks and screw
type terminal blocks
Embases pour borniers
à ressort et borniers à vis

 PR065xxHBBF *(Type 396)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PR075xxHBEL *(Type 337)  V _N 300 V / 17 A V _{max} 250 V / 12 A	 PR075xxHBER *(Type 338)  V _N 300 V / 17 A V _{max} 250 V / 12 A	 PT045xxHBEC *(Type 029)  V _N 300 V / 10 A V _{max} 250 V / 10 A	 PT045xxHBBN *(Type 030)  V _N 300 V / 15 A V _{max} 250 V / 10 A
--	--	--	--	--

Stiftleiste
Pin header
Embases à picots

lötbar
solderable
soudable

entwickelt für THR
designed for THR
conviert pour THR

entwickelt für SMT
designed for SMT
conviert pour CMS

5.00
Rastermaß
Centerline
Pas

Stiftleiste vertikal
Pin header for vertical
mounting
Embase verticale

Stiftleiste vertikal
mit Führung
Shrouded pin header
for vertical mounting
Embase verticale avec
cloison arrière

Stiftleiste vertikal
offene Wanne
Pin header with open
ends for vertical
mounting
Embase verticale sans
cloisons latérales

Stiftleiste vertikal
geschlossene Wanne
Pin header with closed
ends for vertical
mounting
Embase verticale avec
cloisons latérales











Stiftleiste horizontal
offene Wanne
Pin header with open
ends for horizontal
mounting
Embase horizontale
sans cloisons latérales











Stiftleiste horizontal
geschlossene Wanne
Pin header with closed
ends for horizontal
mounting
Embase horizontale
avec cloisons latérales











Tape & Reel möglich
Tape & Reel possible
Emballage en ruban
(Tape & Reel) possible











V_N
Zulassung in
Vorbereitung
Approval pending
Homologation en
cours











180
Seite im Hauptkatalog
page number in
main catalog
numéro de la page du
catalogue principal

 PT045xxHBVC *(Type 031)  V _N 300 V / 10 A V _{max} 250 V / 10 A	 PT055xxHBHC *(Type 039)  V _N 300 V / 15 A SEV Reg 130002 250 V / 6 A	 PT105xxHGDN *(Type 280)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT115xxHBEC *(Type 329)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT115xxHBBN *(Type 330)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A
--	---	--	--	--











 PT115xxHBBF *(Type 336)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT165xxHGDN *(Type 276)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PR015xxVBHC *(Type 017)  V _N 300 V / 15 A SEV Reg 130002 250 V / 10 A	 PR015xxVBVC *(Type 027)  V _N 300 V / 15 A SEV Reg 130002 250 V / 10 A	 PM015xxVBHC *(Type 317)  V _N 300 V / 10 A
--	--	--	--	---

 PM025xxVBHC *(Type 318)  V _N 300 V / 10 A	 PR035xxVBHC *(Type 046)  V _N 300 V / 10 A SEV Reg 130002 250 V / 13.5 A	 PR055xxVBHC *(Type 048)  V _N 300 V / 15 A SEV Reg 130002 320 V / 13.5 A	 PR065xxVBEC *(Type 477)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PR065xxVBBN *(Type 177)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A
--	---	---	---	---

 PR065xxVBFB *(Type 397)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PM035xxVBHC *(Type 417)  V _N 300 V / 15 A	 PT045xxVBEC *(Type 019)  V _N 300 V / 15 A V _{max} 250 V / 10 A	 PT045xxVBBN *(Type 020)  V _N 300 V / 15 A V _{max} 250 V / 10 A	 PT065xxVBEN *(Type 041)  V _N 300 V / 15 A V _{max} 250 V / 10 A
--	---	--	--	--

 PT065xxVBVN *(Type 042)  V _N 300 V / 15 A V _{max} 250 V / 10 A	 PT105xxVGDN *(Type 278)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT115xxVBEC *(Type 319)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT115xxVBBN *(Type 320)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT115xxVBBF *(Type 335)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A
--	--	--	--	--







 PT165xxVGDN *(Type 274)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT175xxVGDN *(Type 270)  V _N 300 V / 15 A	 PR066xxHBEC *(Type 478)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PR066xxHBBN *(Type 178)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT106xxHGDN *(Type 292)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A
--	---	--	--	--

 PT116xxHBEC *(Type 229)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT116xxHBBN *(Type 230)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT116xxHBBF *(Type 236)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PT166xxHGDN *(Type 288)  V _N 300 V / 15 A V _{max} 320 V / 13.5 A	 PR016xxVBHC *(Type 018)  V _N 300 V / 15 A SEV Reg 130002 250 V / 10 A
--	--	--	--	--











Stiftleisten für
Federkraftklemmen und
Schraubklemmen
Pin headers for spring type
terminal blocks and screw
type terminal blocks
Embases pour borniers
à ressort et borniers à vis

 PR016xxVBVC *(Type 028)  300 V / 15 A SEV Req 130002 250 V / 10 A	 PM016xxVBHC  130 V / 10 A 130 V / 10 A	 PR066xxHBBF *(Type 398)  300 V / 15 A 320 V / 13.5 A	 PR066xxVBBF *(Type 399)  300 V / 15 A 320 V / 13.5 A	 PR066xxVBEC *(Type 479)  300 V / 15 A 320 V / 13.5 A
 PR066xxVBBN *(Type 179)  300 V / 15 A 320 V / 13.5 A	 PT106xxVGDN *(Type 290)  300 V / 15 A 320 V / 13.5 A	 PT116xxVBEC *(Type 219)  300 V / 15 A 320 V / 13.5 A	 PT116xxVBBN *(Type 220)  300 V / 15 A 320 V / 13.5 A	 PT116xxVBBF *(Type 235)  300 V / 15 A 320 V / 13.5 A
 PT166xxVGDN *(Type 286)  300 V / 15 A 320 V / 13.5 A	 PT118xxHBEC *(Type 265)  300 V / 15 A / 28 - 14 500 V / 13.5 A	 PT118xxHBBC *(Type 266)  300 V / 15 A / 28 - 14 500 V / 13.5 A	 PT118xxVBEC *(Type 263)  300 V / 15 A / 28 - 14 500 V / 13.5 A	 PT118xxVBBC *(Type 264)  300 V / 15 A / 28 - 14 500 V / 13.5 A
 PT049xxHBVC *(Type 031)  600 V / 10 A 630 V / 10 A	 PT049xxHBBN *(Type 030)  600 V / 15 A 630 V / 10 A	 PT119xxHBBF *(Type 336)  600 V / 15 A 630 V / 13.5 A	 PT069xxVBVN *(Type 042)  600 V / 15 A 630 V / 10 A	 PT049xxVBBN *(Type 020)  600 V / 15 A 630 V / 10 A
 PT119xxVBBN *(Type 320)  600 V / 15 A 630 V / 13.5 A	 PT119xxVBBF *(Type 335)  600 V / 15 A 630 V / 13.5 A	 PT11AxxHBEC *(Type 229)  600 V / 15 A 630 V / 13.5 A	 PT11AxxHBBN *(Type 230)  600 V / 15 A 630 V / 16 A	 PT11AxxHBBF *(Type 236)  600 V / 15 A 630 V / 13.5 A
 PT11AxxVBEC *(Type 219)  600 V / 15 A 630 V / 13.5 A	 PT11AxxVBBN *(Type 220)  600 V / 15 A 630 V / 13.5 A	 PT11AxxVBBF *(Type 235)  600 V / 15 A 630 V / 13.5 A		

Buchsenleisten für
Federkraftklemmen und
Schraubklemmen
Female connectors for spring
type terminal blocks and
screw type terminal blocks
Embases femelles
pour borniers à ressort
et borniers à vis

 FW143xxVBFC  300 V / 10 A 130 V / 10 A	 FT143xxVBFC *(Type 089)  300 V / 10 A 130 V / 10 A	 FT085xxVBFC *(Type 026)  250 V / 6 A
--	--	---

Stiftleisten für
Board-to-Board Verbinder
Pin headers for board-to-board
connectors
Embases pour
connecteurs carte à carte

 PR20BxxHBNN  1.27	 PR20BxxHBDN  1.27	 PR20BxxVBNN  1.27	 PR20BxxVBDN  1.27	 PM20BxxVBNN  1.27
--	--	---	--	--




Stiftleisten für
Board-to-Board Verbinder
Pin headers for
board-to-board connectors
Embases pour
connecteurs carte à carte

 PM20BxxVBDN Icons: THR, 1.27, SMD, 2.00	 PR20CxxHBNN Icons: THR, 2.00, SMD, 2.00	 PR20CxxHBDN Icons: THR, 2.00, SMD, 2.00	 PM20CxxHBNN Icons: THR, 2.00, SMD, 2.00	 PM20CxxHBDN Icons: THR, 2.00, SMD, 2.00
 PR20CxxVBNN Icons: THR, 2.00, SMD, 2.00	 PR20CxxVBDN Icons: THR, 2.00, SMD, 2.00	 PM20CxxVBNN Icons: THR, 2.00, SMD, 2.00	 PM20CxxVBDN Icons: THR, 2.00, SMD, 2.00	 PR202xxHBNN Icons: THR, 2.54, SMD, 2.00
 PR202xxHBDN Icons: THR, 2.54, SMD, 2.00	 PM202xxHBNN Icons: THR, 2.54, SMD, 2.00	 PM202xxHBDN Icons: THR, 2.54, SMD, 2.00	 PR202xxVBNN Icons: THR, 2.54, SMD, 2.00	 PR202xxVBDN Icons: THR, 2.54, SMD, 2.00
 PM202xxVBNN Icons: THR, 2.54, SMD, 2.00	 PM202xxVBDN Icons: THR, 2.54, SMD, 2.00			






Buchsenleisten für
Board-to-Board Verbinder
Female connectors for
board-to-board connectors
Embases femelles pour
connecteurs carte à carte



 FR20BxxVBNN Icons: THR, 1.27, SMD, 2.00	 FR20BxxVBDN Icons: THR, 1.27, SMD, 2.00	 FM20BxxVBDN Icons: THR, 1.27, SMD, 2.00	 FR20CxxHBNN Icons: THR, 2.00, SMD, 2.00	 FR20CxxHBDN Icons: THR, 2.00, SMD, 2.00
 FR20CxxVBNN Icons: THR, 2.00, SMD, 2.00	 FR20CxxVBDN Icons: THR, 2.00, SMD, 2.00	 FM20CxxVBNN Icons: THR, 2.00, SMD, 2.00	 FM20CxxVBDN Icons: THR, 2.00, SMD, 2.00	 FR202xxHBNN Icons: THR, 2.54, SMD, 2.00
 FR202xxHBDN Icons: THR, 2.54, SMD, 2.00	 FR202xxVBNN0002 Icons: THR, 2.54, SMD, 2.00	 FR202xxVBDN0002 Icons: THR, 2.54, SMD, 2.00	 FR202xxVBNN Icons: THR, 2.54, SMD, 2.00	 FR202xxVBDN Icons: THR, 2.54, SMD, 2.00
 FR202xxVBNN0001 Icons: THR, 2.54, SMD, 2.00	 FR202xxVBDN0001 Icons: THR, 2.54, SMD, 2.00	 FM202xxVBNN Icons: THR, 2.54, SMD, 2.00	 FM202xxVBDN Icons: THR, 2.54, SMD, 2.00	

RJ45 für Geräteanschluss
 RJ45 modules
 for device connection
 RJ45 pour raccordement
 d'appareils

 232	 232	 233
PCB Edge Connector vertical	PCB Edge Connector horizontal	PCB Edge Connector horizontal for SFP
geschirmt shielded blindé	geschirmt shielded blindé	geschirmt shielded blindé

RJ45 ungeschirmt
 RJ45 unshielded
 RJ45 non blindé






 235	 235	 236	 237	 237
AJS59L	AJT60A	AJT65A	AJT84A	AJS56A
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport stehend Single port top entry Monoport vertical	Einzelport stehend Single port top entry Monoport vertical



 238	 239
AJT42C	AJT47C
Multiport liegend Multiport side entry Multiport horizontal	Multiport stehend Multiport top entry Multiport vertical

RJ45 geschirmt
 RJ45 shielded
 RJ45 blindé

 240	 240	 241	 241	 242
AJT92B8813 Magnetics 10/100 MBit	AJT92BC813 Magnetics 1 GBit	AJT65B	AJT94B	AJT75B, 10P/8C
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal

 242	 243	 243	 244	 244
AJT75B, 10P/10C	AJS58B	AJS59L	AJT93B	AJT74B
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport stehend Single port top entry Monoport vertical	Einzelport stehend Single port top entry Monoport vertical

 245	 246	 246	 247	 247
AJT01B	AJT47D	AJT93D	AJT48D	AJT49D
Einzelport stehend Single port top entry Monoport vertical	Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal

 248	 248
AJT46D	AJT52D
Multiport stehend Multiport top entry Multiport vertical	Multiport stehend Multiport top entry Multiport vertical





RJ45 LED ungeschirmt
 RJ45 LED unshielded
 RJ45 DEL non blindé

 249	 249	 250	 251	 252
AJT18L	AJT31L	AJT40L	AJT36L	AJT32L
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport stehend Single port top entry Monoport vertical	Multiport liegend Multiport side entry Multiport horizontal	Multiport stehend Multiport top entry Multiport vertical


RJ45 LED ungeschirmt
RJ45 LED unshielded
RJ45 DEL non blindé

 AJT33L	 AJT34L	 AJT38L	 AJT39L	 AJT35L
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport stehend Single port top entry Monoport vertical	Einzelport stehend Single port top entry Monoport vertical	Multiport liegend Multiport side entry Multiport horizontal






RJ45 LED geschirmt
RJ45 LED shielded
RJ45 DEL blindé




 AJT37L	 AJT41L	 AJT43L	 AJT44L
Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal	Multiport liegend Multiport side entry Multiport horizontal

RJ45 Stecker
RJ45 plugs
Connecteurs mâle RJ45



 AJP92A
Einzelport stehend Single port top entry Monoport vertical

RJ12






 AJT85A	 AJT87A	 AJS57A	 AJT84A	 AJS55A
Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport liegend Single port side entry Monoport horizontal	Einzelport stehend Single port top entry Monoport vertical	Einzelport stehend Single port top entry Monoport vertical






 AJT46C	 AJT43C 1x2 Port	 AJT43C 1x4 Port
Multiport liegend Multiport side entry Multiport horizontal	Multiport stehend Multiport top entry Multiport vertical	Multiport stehend Multiport top entry Multiport vertical

RJ11


 AJS55A	 AJT87A
Einzelport stehend Single port top entry Monoport vertical	Einzelport liegend Single port side entry Monoport horizontal

USB

 AJT21G	 AJT24G	 AJT25G	 AJT33G	 AJS05G
Typ A liegend Type A side entry Type A horizontal	Typ A liegend Type A side entry Type A horizontal	Typ A liegend Type A side entry Type A horizontal	Typ A liegend Type A side entry Type A horizontal	Typ A liegend Type A side entry Type A horizontal

 AJT20G	 AJT27G	 AJT30G	 AJS08G	 AJS09G
Typ A stehend Type A top entry Type A vertical	Typ A stehend Type A top entry Type A vertical	Typ B liegend Type B side entry Type B horizontal	Typ B liegend Type B side entry Type B horizontal	Typ B liegend Type B side entry Type B horizontal

USB




247

AJT14G

Typ B stehend
Type B top entry
Type B vertical


Ethernet M12



277

MMW360A1A1


Buchsen D-kodiert
Jacks D-coded
Connecteurs femelles codés D



277

MMW370A1A1


Buchsen D-kodiert
Jacks D-coded
Connecteurs femelles codés D



278

MMT471A115

Buchsen D-kodiert
Jacks D-coded
Connecteurs femelles codés D



279

MMT361A315


Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



279

MMT361A315-0009

Buchsen X-kodiert IP67 offen
Jacks X-coded IP67 unmated
Connecteurs femelles codés X



279

MMT371A3B5


Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



279

MMT371A3B5-0009


Buchsen X-kodiert IP67 offen
Jacks X-coded IP67 unmated
Connecteurs femelles codés X



280

MMT060A315


Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



280

MMT471A315

Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



280

MMT471A315-0001


Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



281

MMT471A315-0002


Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X



281

**MMT471A315
in individual parts**

Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X




281

MMTA70A315

Buchsen X-kodiert
Jacks X-coded
Connecteurs femelles codés X

Zubehör
Accessories
Accessoires



285

**Mounting flange
710084 | right**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



285

**Mounting flange
710085 | left**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



286

**Mounting flange
750150 | right**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



286

**Mounting flange
750151 | left**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



287

**Mounting flange
750313 | right**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



287

**Mounting flange
750314 | left**

Befestigungsflansche schraubbar
Mounting flanges, screwable
Brides, vissables



288

**Mounting flange 720158
| lock depth 1.5 mm**

Befestigungsflansche rastbar
Mounting flanges, latchable
Brides, enclenchables



289

**Mounting flange 720036
| lock depth 1 mm**


Befestigungsflansche rastbar
Mounting flanges, latchable
Brides, enclenchables



289

**Mounting flange 720036
| lock depth 1.5 mm**


Befestigungsflansche rastbar
Mounting flanges, latchable
Brides, enclenchables



290

**Coding pin 710121 |
short**

Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle



290

**Coding pin 710122 |
long**


Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle



291

**Coding pin 720159 |
short**


Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle



291

**Coding pin 720159 |
long**


Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle



293

**Coding pin 716846 |
blue**

Kodierstifte mit Polverlust
Coding pins with loss of a pole
Pions de codage avec perte de pôle



293

**Coding pin 716906 |
orange**


Kodierstifte mit Polverlust
Coding pins with loss of a pole
Pions de codage avec perte de pôle



294

**Protection against
accidental contact 711401**

Sonstiges
Other
Autres



294

Jumper 711047

Sonstiges
Other
Autres



295

**LED light transmitter
|Centerline 3.50 mm**


LED Lichtleiter
LED light transmitter
Transmetteur de luminosité DEL



295

**LED light transmitter
|Centerline 3.81 mm**

LED Lichtleiter
LED light transmitter
Transmetteur de luminosité DEL




296


**Coding pin 720293 |
black**

Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle


Zubehör
Accessories
Accessoires

 296


Coding pin 720243 | black




Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle

 297


Coding pin 720243 | gray




Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle

 297


Coding pin 720024 | white | Pin header



Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle

 298

Coding pin 720025 | white | Terminal block



Kodierstifte ohne Polverlust
Coding pins without loss of a pole
Pions de codage sans perte de pôle

 299

Screwdriver 791989 | 2.5 mm



Klinge Schlitz
Blade slotted
Lame fente

 299

Screwdriver 791990 | 3.0 mm



Klinge Schlitz
Blade slotted
Lame fente

METZ CONNECT GmbH ist Mitglied in folgenden Organisationen und Verbänden.
 METZ CONNECT GmbH is member in the following organizations and associations.
 METZ CONNECT GmbH est adhérent aux commissions et organismes suivants.



METZ CONNECT USA Inc.
 200 Tornillo Way
 Tinton Falls, NJ 07712
 USA
 Phone +1-732-389-1300
 Fax +1-732-389-9066

METZ CONNECT France SAS
 28, Rue Schweighaeuser
 67000 Strasbourg
 France
 Phone +33 3886 170 73
 Fax +33 3886 194 73

METZ CONNECT Zhongshan Ltd.
 Ping Chang Road
 Ping Pu Industrial Park
 Sanxiang Town
 Zhongshan City, 528463
 Guangdong Province
 China
 Phone +86 760 86365 055
 Fax +86 760 86365 050

METZ CONNECT Asia Pacific Ltd.
 Suite 1803, 18/F
 Chinachem Hollywood Centre,
 1 Hollywood Road, Central
 Hong Kong
 Phone +852 26 027 300
 Fax +852 27 257 522

METZ CONNECT GmbH

Im Tal 2
 78176 Blumberg
 Germany
 Phone +49 7702 533-0
 Fax +49 7702 533-189
 info@metz-connect.com
 www.metz-connect.com

