

Wire Rope Cutter

95

Compact size, lightweight, high performance level
High transmission joint design makes cutting 20% easier
Box joint design for greater stability

- > for cutting high-strength wire ropes up to up to 5/32" (4 mm) and cable 3/16" (6 mm)
- > at just 6 1/4" (160 mm) length this tool is considerably more powerful than many larger wire rope cutters
- > included thumb lock and opening spring
- > ball bearing steel for a long service life
- > induction hardened cutting edges
- > cuts cleanly and evenly without wire ends splaying or fanning out



95 62 160



Product Number	Packaging	↔ Inch mm		Head	Handles	⊕ Ø Inch Ø mm	⊙ Ø Inch Ø mm	⚖ lbs
95 62 160	X	6 1/4 160	⊕ ⊙ ⊠ ⊡ ⊢	polished	multi-component grips	3/16 6.0	5/32 4.0	0.38

Cable Cutters for Wire Rope and ACSR

95

- > for ACSR, wire ropes, steel rods, copper and aluminum cables
- > suitable for cutting overhead cables with strain relief wire
- > angular cutting blades prevent fanning out
- > optimum transmission ratio for high cutting performance
- > bolted cutter head, replaceable
- > lightweight
- > cutter head: high-grade special tool steel, multi stage oil-hardened
- > handles: aluminum, high-strength

95 81 600

With reinforced cutter head for higher performance, also cuts piano wire



95 71 600



95 77 600



WARNING: This product can expose you to chemicals including Diisononyl Phthalate, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Product Number	Packaging	↔ Inch mm		Head	Handles	Cutting capacities				AWG	⚖ lbs
						⊕ mm ²	⊙ Ø Inch Ø mm	◐ Ø Inch Ø mm	● Ø Inch Ø mm		
95 71 445		17 1/2 445	⊕ ⊙ ⊠ ⊡ ⊢	polished	plastic grips	95	25/64 10	9/32 7	-	3/0	2.39
95 71 600		23 5/8 600	⊕ ⊙ ⊠ ⊡ ⊢	polished	plastic grips	150	35/64 14	23/64 9	-	5/0	3.84
95 77 600		23 5/8 600	⚠ 1000V ⊕ ⊙ ⊠ ⊡ ⊢	polished	plastic dipped insulated, VDE-tested	150	35/64 14	23/64 9	-	5/0	5.02
95 81 600		23 5/8 600	⊕ ⊙ ⊠ ⊡ ⊢	polished	plastic grips	150	5/8 16	25/64 10	11/64 4.5	5/0	4.97

95 79 445 Spare cutter head for 95 71 445

95 79 600 Spare cutter head for 95 71 600 / 95 77 600

95 89 600 Spare cutter head for 95 81 600