

# Electronics Diagonal Cutters

DIN ISO 9654

75

- > bolted joint for high precision and stress tolerance
- > for ultra fine cutting work, e.g. in electronics and fine mechanics
- > sharp, ground cutting edges for soft, hard wire and piano wire
- > cutting edge hardness (approx. 64 HRC)
- > low-friction double spring for gentle and even opening
- > high-grade special tool steel; forged, multi stage oil-hardened

## Style 0

With bevel

## Style 1

With bevel and lead catcher, no uncontrolled loss of cut wire ends

## Style 2


With small bevel

## Style 3

Particularly narrow head, with bevel



Bolted joint



75 02 125



75 12 125



75 22 125



75 52 125

**WARNING:** This product can expose you to chemicals including Diisononyl Phthalate, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

| Product Number | Packaging | ↔<br>Inch<br>mm |  | Style | Pliers    | Handles       | Cutting capacities       |                    |                    |                    | Dimensions      |                 |                 | <br>lbs |
|----------------|-----------|-----------------|--|-------|-----------|---------------|--------------------------|--------------------|--------------------|--------------------|-----------------|-----------------|-----------------|---------|
|                |           |                 |  |       |           |               | <br>Ø Inch<br>Ø mm       | <br>Ø Inch<br>Ø mm | <br>Ø Inch<br>Ø mm | <br>Ø Inch<br>Ø mm | A<br>Inch<br>mm | B<br>Inch<br>mm | D<br>Inch<br>mm |         |
| 75 02 125      |           | 5<br>125        |  | 0     | burnished | plastic grips | 1/64 - 3/64<br>0.2 - 1.3 | 3/64<br>1.0        | 1/32<br>0.6        | 1/64<br>0.4        | 13/32<br>10.5   | 35/64<br>14     | 1/4<br>6.5      | 0.18    |
| 75 12 125      |           | 5<br>125        |  | 1     | burnished | plastic grips | 1/64 - 3/64<br>0.2 - 1.3 | 3/64<br>1.0        | 1/32<br>0.6        | 1/64<br>0.4        | 13/32<br>10.5   | 35/64<br>14     | 1/4<br>6.5      | 0.18    |
| 75 22 125      |           | 5<br>125        |  | 2     | burnished | plastic grips | 1/64 - 3/64<br>0.2 - 1.3 | 1/32<br>0.9        | 1/64<br>0.4        | 1/64<br>0.3        | 13/32<br>10.5   | 35/64<br>14     | 1/4<br>6.5      | 0.18    |
| 75 52 125      |           | 5<br>125        |  | 3     | burnished | plastic grips | 1/64 - 1/32<br>0.2 - 0.8 | 1/64<br>0.5        | 1/64<br>0.3        | -                  | 13/32<br>10.5   | 35/64<br>14     | 1/4<br>6.5      | 0.18    |