

M23 P male-c 2mm (0,75-2,5mm²) Au



| Part number | 09 15 600 6121 |
|--------------------|-------------------------------------|
| Specification | M23 P male-c 2mm (0,75–2,5mm²) Au |
| HARTING eCatalogue | https://b2b.harting.com/09156006121 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Contacts |
|----------------------------|-------------------------|
| Series | Circular connectors M23 |
| Identification | Power |
| Type of contact | Crimp contact |
| Description of the contact | 2 mm |

Version

| Gender | Male |
|-----------------------|-----------------|
| Manufacturing process | Turned contacts |

Technical characteristics

| Conductor cross-section | 0.75 2.5 mm² |
|-------------------------|--------------|
| Operating current | ≤28 A |
| Contact resistance | ≤3 mΩ |
| Stripping length | 7 mm |

Material properties

| Material (contacts) | Copper alloy |
|---------------------|--|
| Surface (contacts) | Gold plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Material properties

| REACH Annex XVII substances | Not contained |
|--------------------------------------|--------------------------------------|
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 339476a1-86ba-49e9-ab4b-cd336420d72a |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead |

Specifications and approvals

| Specifications | EN 60664-1 |
|----------------|------------|
| Specifications | IEC 61984 |

Commercial data

| Packaging size | 100 |
|--------------------------------|--|
| Net weight | 0.1 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| eCl@ss | 27440204 Contact for industrial connectors |