





- > Stainless steel offers corrosion resistance
- > 80% anti-magnetic (20% magnetic dues to weld during manufacturing)
- > Needle-point tips offer extra-fine gripping on very small components and wire
- > ESD handles discharge electrostatic energy through the handles in a gradual and controlled manner (Dissipative $10^4/10^9$ OHM regarding DIN EN 61340-5-1)




92 21 01 ESD, 92 21 07, 92 22 06,
92 22 07, 92 28 69 ESD and
92 28 70 ESD



92 22 12 and 92 28 71 ESD



92 21 03 ESD and 92 21 08



92 32 29 and 92 38 75 ESD

	Product Number	Length	Width	Height	Finish	Style	Gripping Surface	Tip (A)	Tip (B)
	92 21 01 ESD	5"	7/16"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.20 mm	0.25 mm
	92 21 03 ESD	5 1/2"	5/16"	9/16"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.20 mm	0.30 mm
	92 21 07	4 3/8"	3/8"	3/8"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.20 mm	0.25 mm
	92 21 08	5 1/2"	5/16"	1/2"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.20 mm	0.30 mm
	92 22 06	4 3/4"	3/8"	7/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.25 mm	0.25 mm
	92 22 07	5"	7/16"	3/8"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.20 mm	0.25 mm
	92 22 12	4 3/8"	3/8"	7/16"	stainless steel, 80% anti-magnetic, acid resistant	straight	smooth	0.20 mm	0.20 mm
	92 28 69 ESD	4 3/4"	3/8"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.25 mm	0.25 mm
	92 28 70 ESD	4 3/8"	3/8"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.20 mm	0.25 mm
	92 28 71 ESD	4 3/8"	3/8"	1/2"	stainless steel, 80% anti-magnetic, acid resistant, ESD	straight	smooth	0.20 mm	0.20 mm
	92 32 29	4 5/8"	3/8"	3/8"	stainless steel, 80% anti-magnetic, acid resistant	35° angled	smooth	0.25 mm	0.30 mm
	92 38 75 ESD	4 5/8"	3/8"	3/8"	stainless steel, 80% anti-magnetic, acid resistant, ESD	35° angled	smooth	0.25 mm	0.30 mm